MAXXUS ATF-MB-MULTI

last revision: 04.05.2011 / date: 01.07.11



1. Substance/ Product Identification

Product Trade Name: MAXXUS ATF-MB-MULTI

Address: Wiget Autoteile GmbH & Co KG

Kirchheider Str. 139 32657 Lemgo Germany

Emergency Phone Number: +49- 5264-6483-40

Product type: ATF

2. Hazards Identification

Principal Hazards: If the product comes in contact with skin, eyes flush immediately with plenty of

water. In case of swallowing please contact the physician.

Labelling: --

Dangerous compounds: see chapter 3; R-sentence descriptions, see chapter 16.

Additional advices / hints: Please advise the personal stuff of the a.m. product components.

3. Composition/Information on Ingredients

Hazardous Ingredients (in acc. to Dangerous Preparation Directive 1999/45/EC)

Components	Wt-%	Labels	R-phrases	EU-No.
Alkylphosphite derivatives	<0.18	Xi	R36/38	217-316-1
Diphenylamine derivatives	<0.1	N, T	R23/24/25, R33, R50/53	204-539-4

4. First Aid Measures

Ingestion: DO NOT INDUCE VOMITING. If conscious, give 2 glasses of water. Get

immediate medical attention.

Eyes: Flush immediately with water for at least 15 minutes. Get immediate medical

attention.

Skin: Wash with soap and water. Remove contaminated clothing. Get medical

attention of irritation develops. Launder contaminated clothing before reuse.

Inhalation: Remove exposed person to fresh air if adverse effects are observed.

Additional Information: Note to physician: Treat symptomatically.

5. Fire Fighting Measures

Flash Point: >170°C COC (typically)

Extinguishing Media: CO2, dry chemical, or foam. Water can be used to cool and protect exposed

material.

Fire Fighting Procedures: Recommend wearing self-contained breathing apparatus. Water may cause

splattering.

Unusual Fire &

Explosion Hazards: Toxic fumes, gases (H2S, CO, CO2, NOx, SOx etc.) or vapours may evolve

on burning.

6. Accidental Release Measures

Spill Procedures: Personal Protective Equipment must be worn, see Personal Protection

Material Safety Data Sheet acc. to 2001/58/EC

MAXXUS ATF-MB-MULTI

last revision: 04.05.2011 / date: 01.07.11



Section for PPE recommendations. Ventilate area if spilled in confined space or other poorly ventilated areas. Prevent entry into sewers and water-ways. Pick up free liquid for recycle/ disposal. Residual liquid can be absorbed on inert material. Check under Transportation and Labelling (DOT/CERCLA) and Other Regulatory Information Section (SARA) for hazardous Substances to determine regulatory reporting requirement for spills.

7. Handling and Storage

Loading Temperature: Not determined.

Maximum Handling: Max. 60°C.

Temperature

Handling Procedure: Keep containers closed when not in use. Wash thoroughly after handling.

Empty container contains product residue which may exhibit hazards of

product.

Maximum Storage

Temperature: Not determined.

Storage Procedures: No special storage precautions required.

Handling Procedures: Protective goggles and gloves are recommended.

Avoid contact with skin or eyes.

8. Exposure Controls/ Personal Protection

Exposure Limits Diphenylamine (CAS-No. 122-39-4)

Long-term (8h TWA): 10mg/m³, short-term (25 min. TWA): 20mg/m³

Other Exposure Limits: Under decomposition temperature H2S may be generated. Under these

conditions which may generate H2S, observe the ACGIH STEL of 14mg/m3

(10ml/m³).

Ventilation Procedures: Use local exhaust ventilation to control mists or vapors.

Hand Protection: Nitrile rubber.

Eye Protection: Chemical goggles or face shield.

Respiratory Protection: Use full face respirator with a combination organic vapor and dust/ mist

cartridge if the recommended exposure limit is exceeded.

Clothing

Recommendation: A long sleeve shirt is recommended.

9. Physical and Chemical Properties

Appearance: Dark red (or colourless) liquid

Smell: Characteristically

Flash Point: >170°C COC

Upper Flammable Limit: Not determined Vol-%

Lower Flammable Limit: Not determined Vol-%

Auto Ignition Point: Not determined.

Explosion Data: Material does not have explosive properties.

Vapour Pressure: Not Determined.

Material Safety Data Sheet acc. to 2001/58/EC

MAXXUS ATF-MB-MULTI

last revision: 04.05.2011 / date: 01.07.11



pH: Not determined.

Specific Gravity: 0.85 g/cm³ (@15.6°C) typically

Water Solubility: Insoluble.

Evaporation Rate: Not determined.

Viscosity: 31 mm²/s (@40°C), typically

Odour Threshold Unknown.

Boiling Point: Not determined.

Pour Point Temperature: max. -42°C

10. Stability and Reactivity

Stability: Material is normally stable at moderately elevated temperatures and

pressures.

Decomposition

Temperature: Toxic fumes may occur at temperatures above 65°C.

Incompatibility: Oxidizing agents, Halogens and halogenated compounds.

Polymerization: Will not occur.

Thermal Decomposition: Smoke, carbon monoxide, carbon dioxide, aldehydes and other products of

incomplete combustion. Oxides of C-, N- or S- may occur.

11. Toxicological Information

Acute Exposure-

Eye Irritation: Prolonged contact may lead to eye irritating, but the product is not a primary

eye irritant.

Skin Irritation: Based on data from components or similar materials like other motor oils.

Prolonged or repeated skin contact as from clothing wet with material may cause skin irritations and or allergic skin reactions like redness, edema,

drying, and cracking of the skin.

Respiratory Irritation: If material is misted or if vapours are generated from heating, exposure may

cause irritation of mucous membranes and the upper respiratory tract similar to that observed with mineral oil. Based on data from components or similar materials. Under good industrial hygiene practises where all exposure limits

are observed, respiratory irritation should not be problem.

Dermal Toxicity: No data available.

Inhalation Toxicity: No data available.

Oral: No data available.

Dermal Sensitization: No data available to indicate product or components may be a primary skin

sensitizer. Therefore longer contact should be avoided.

Inhalation Sensitization: No data available to indicate product or components may be respiratory

sensitizers.

MAXXUS ATF-MB-MULTI

last revision: 04.05.2011 / date: 01.07.11



Chronical Exposure –

Chronic Toxicity: No data available.

Carcinogenicity: This product is formulated with mineral oils which are are considered to be

severely refined and not considered to be carcinogenic under IARC.

All of the oils in this product have been demonstrated to contain <3% extracts

by the IP 346 test.

Mutagenicity: No data available.

Reproductive Toxicity: No data available.

Teratogenicity: No data available.

Other: No other health hazards known.

12. Ecological Information

Environmental Toxicity-

Freshwater Fish

Toxicity: Not determined.

Freshwater Invertebrates

Toxicity:

Not determined.

Algae Toxicity: Not determined.

Saltwater Fish Toxicity: Not determined.

Saltwater Invertebrates:

Toxicity: Not determined.

Bacteria Toxicity: Not determined...

Miscellaneous Toxicity: Not determined.

Environmental Fate –

Biodegradation: Laboratory studies indicate limited biodegradation with non- acclimated

sludge, based on component data.

Bioaccumulation: Not determined.

Soil Mobility: Not determined.

WGK / WPC: Estimated: WGK 2 (WPC 2) acc. to German regulations.

13. Disposal Consideration

Waste Disposal: In accordance with European Law: No dangerous disposal.

14. Transport Information

ICAO/ IATA: Not regulated.

IMDG (Ambient): Not regulated.

IMDG (Elevated): Not regulated.

MAXXUS ATF-MB-MULTI

last revision: 04.05.2011 / date: 01.07.11



IMDG EMS: Not applicable.

IMDG MFAG: Not applicable.

IMO Marine Bulk: Product contains heterocyclic ethers of Class 9, UN 3082 PG III

ADR/ RID (Ambient): Not regulated.

ADR/ RID (Elevated): Not regulated.

15. Regulatory Information

Symbol(s):

Indication of danger: -

Precautionary Labels: S37/S39 Wear suitable gloves & goggles.

S26 Flush with plenty of water, immediately after contamination.

S24 Avoid skin contact.

[Product contains: Smaller amounts of Alkylthiadiazol- & Diphenylamine derivatives]

16. Other Information

R-phrases, mentioned under chapter 3 but irrelevant for this final product:

R23/24/25 Toxic by inhalation, in contact with skin if swallowed

R33 Danger of commutative effects
R36/38 Irritating to eyes and skin

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

