



ANTIFREEZE/COOLANT SUPER PLUS PREMIUM

SAFETY DATA SHEET

according to Regulation (EU) 2015/830

ISSUE DATE: 02.03.2015
REVISION DATE: 23.10.2018
SUPERSEDES DATE: 02.03.2015
VERSION: 2.0

1. SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name	Antifreeze/Coolant Super Plus Premium
Product code	Ford Internal Ref.: 194810
SDS Number	5532
Product use	Public use

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Anti-Freeze and De-icing products
Uses advised against	None known

1.3. Details of the supplier of the safety data sheet

Supplier Ford-Werke GmbH Edsel-Ford-Str. 2-14 50769 Cologne Germany +49 221 90-33333 sdseu@ford.com	Distributor Ford Motor Company Ltd. Parts Distribution Centre Royal Oak Way South NN11 8NT Daventry, Northants United Kingdom +44 1327 305 198
--	---

1.4. Emergency telephone number

+49 (0) 6132-84463 (GBK GmbH – 24/7)

2. SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008

Health hazards	Acute toxicity (oral), Category 4	H302	Harmful if swallowed.
	Specific target organ toxicity — Repeated exposure, Category 2	H373	May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008

Hazard pictograms



Signal word	Warning
Contains	Ethandiol

Hazard statements

H302	Harmful if swallowed.
H373	May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).

Precautionary statements

General

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

Prevention

P260 Do not breathe vapours, mist.
P264 Wash hands thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.

Response

P314 Get medical advice/attention if you feel unwell

Disposal

P501 Dispose of contents and container to an approved waste disposal plant.

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII.

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.

3. SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical name	CAS- No EC- No Index No RRN	%	Classification according to Regulation (EC) No. 1272/2008	Notes
Ethandiol	107-21-1 203-473-3 603-027-00-1 01-2119456816-28-XXXX	80 - < 98	Acute Tox. 4 (Oral), H302 STOT RE 2, H373	substance with a Community workplace exposure limit
Sodium 2-ethylhexanoate	19766-89-3 243-283-8	0,1 - < 3	Repr. 2, H361d	

Full text of H-statements: see section 16

4. SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

Skin contact: Gently wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

Eyes contact Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minutes minimum). Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Do not induce vomiting. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation In high concentrations : May cause respiratory irritation.

Symptoms/effects after skin contact Repeated or prolonged skin contact may cause irritation. Dry skin.

Symptoms/effects after eye contact Exposure may cause temporary irritation, redness, or discomfort.

Symptoms/effects after ingestion May be harmful if swallowed. Repeated contact. May affect kidneys. Overexposure may result in : Convulsions. Dizziness. Nausea. Vomiting. Abdominal pain. Swelling. Prolonged exposure may cause chronic effects.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

5. SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Alcohol resistant foam. Dry powder. Carbon dioxide.
Unsuitable extinguishing media	Do not use a water jet since it may cause the fire to spread.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products	Toxic fumes may be released. Carbon oxides (CO, CO ₂).
-------------------------------	--

5.3. Advice for firefighters

Firefighting instructions	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if it can be done without personal risk. Ensure adequate ventilation, especially in confined areas.
Protection during firefighting	Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

6. SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Protective equipment	Wear appropriate protective equipment and clothing during clean-up. For personal protection, see section 8 of the SDS.
Emergency procedures	Evacuate area. Keep people away from and upwind of spill/leak. Avoid breathing mist or vapor. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

For emergency responders

Protective equipment	Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	Evacuate unnecessary personnel. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

For containment	Stop leak without risks if possible.
Methods for cleaning up	Use water spray to reduce vapors or divert vapor cloud drift. Small spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Never return spills in original containers for re-use. Local authorities should be advised if significant spillages cannot be contained.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of residues refer to section 13: "Disposal considerations". For further information refer to section 13.

7. SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	Ensure good ventilation of the work station. Avoid prolonged exposure. Wear personal protective equipment.
Hygiene measures	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	Store in a well-ventilated place. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS). Keep out of reach of children.
Incompatible materials	Strong oxidizing agent.

7.3. **Specific end use(s)** Anti-Freeze and De-icing products.

8. SECTION 8: Exposure controls/personal protection

8.1. Control parameters

EU

Regulation	Substance	Type	Value
COMMISSION DIRECTIVE 2000/39/EC	Ethandiol (107-21-1) Ethylene glycol	IOELV TWA	52 mg/m ³ Vapours
		IOELV TWA	20 ppm Vapours
		IOELV STEL	104 mg/m ³ Vapours
		IOELV STEL	40 ppm Vapours
		Notes	Skin

United Kingdom

Regulation	Substance	Type	Value
EH40. HSE	Ethandiol (107-21-1) Ethane-1,2-diol	WEL TWA	52 mg/m ³ Vapours 10 mg/m ³ Particulates
		WEL TWA	20 ppm vapour
		WEL STEL	104 mg/m ³ vapour
		WEL STEL	40 ppm vapour
		Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)

DNEL: Derived no effect level

No data available

Components	Type	Route	Value	Form
Ethandiol (107-21-1)	Worker	Dermal	106 mg/kg bodyweight/day	Long-term - systemic effects
		Inhalation:	35 mg/m ³	Long-term - local effects
	Consumer	Dermal	53 mg/kg bodyweight/day	Long-term - systemic effects
		Inhalation:	7 mg/m ³	Long-term - local effects

PNEC: Predicted no effect concentration

No data available

Components	Type	Route	Value	Form
Ethandiol (107-21-1)	Not applicable	Freshwater	10 mg/l	
		Seawater	1 mg/l	
		sediment	37 mg/kg dwt	Freshwater
		sediment	3.7 mg/kg dwt	Seawater
		Soil	1.53 mg/kg dwt	
		STP	199.5 mg/l	

8.2. Exposure controls

Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level		
Materials for protective clothing	Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment		
Individual protection measures, such as personal protective equipment (PPE)			
Eye protection	Safety glasses with side shields. EN 166.		
Skin protection			
Hand protection	EN 374. Protective gloves. The recommendation is only valid for the supplied product and the stated application. Special working conditions, like heat or mechanical strain, which deviate from the test conditions, can reduce the protective effect provided by the recommended glove		
Material	Permeation	Thickness (mm)	Comments
Nitrile rubber (NBR)	6 (> 480 minutes)	0,4	Glove recommendation: Camatril Velours® 730 (Kächele-Cama GmbH, source of supply see www.kcl.de) or comparable product.
In case of splash contact: Nitrile rubber (NBR)	6 (> 480 minutes)	0,4	Glove recommendation: Camatril Velours® 730 (Kächele-Cama GmbH, source of supply see www.kcl.de) or comparable product.
Other protective measures	Normal work clothing (long sleeved shirts and long pants) is recommended.		
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment. Combinationfilter A-P2		
Thermal hazard protection	Wear appropriate thermal protective clothing, when necessary.		
Environmental exposure controls	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases.		
Consumer exposure controls	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.		

9. SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Liquid.
Colour	orange.
Odour	mild.
Odour threshold	No data available
pH	8.6 @ 20°C
Relative evaporation rate (butylacetate=1)	No data available
Melting point	No data available
Freezing point	-18 °C (-0,4 °F)
Boiling point	>= 175 °C (>= 347 °F)
Flash point	122 °C (251,6 °F) Closed cup (Pensky-Martens)
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Flammability (solid, gas)	Not applicable
Vapour pressure	No data available
Relative vapour density at 20 °C	No data available
Relative density	No data available
Density	1.113 kg/l @ 20°C
Solubility	Soluble in water.
Log Pow	No data available
Viscosity, kinematic	No data available

Viscosity, dynamic	No data available
Explosive properties	No data available
Oxidising properties	No data available
Explosive limits	No data available

9.2. Other information

VOC (EU)	0 %
----------	-----

10. SECTION 10: Stability and reactivity

10.1. Reactivity	The product is non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reactions known under normal conditions of use.
10.4. Conditions to avoid	Contact with incompatible materials.
10.5. Incompatible materials	Strong acids. Peroxides. Strong oxidizing agents. Nitrates. Chlorates.
10.6. Hazardous decomposition products	During fire, gases hazardous to health may be formed. Carbon oxides (CO, CO ₂). Elevated temperature. Ketones. Aldehydes.

11. SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity Oral: Harmful if swallowed.

Mixture

Name	Method	Type	Exposure route	Value	Unit	Species	Remarks
Antifreeze/Coolant Super Plus Premium	(calculated value)	ATE	oral	531,9	mg/kg		

Substance

Name	Method	Type	Exposure route	Value	Unit	Species	Remarks
Ethandiol (107-21-1)		ATE	oral	500	mg/kg		

Skin corrosion/irritation	Based on available data, the classification criteria are not met
Serious eye damage/irritation	Based on available data, the classification criteria are not met
Respiratory or skin sensitisation	Based on available data, the classification criteria are not met
Germ cell mutagenicity	Based on available data, the classification criteria are not met
Carcinogenicity	Based on available data, the classification criteria are not met
Reproductive toxicity	Based on available data, the classification criteria are not met
STOT-single exposure	Based on available data, the classification criteria are not met
STOT-repeated exposure	May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).
Aspiration hazard	Based on available data, the classification criteria are not met

12. SECTION 12: Ecological information

12.1. Toxicity

Ecology - general The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

12.2. Persistence and degradability

Antifreeze/Coolant Super Plus Premium

Persistence and degradability Expected to be biodegradable.

12.3. Bioaccumulative potential

Ethandiol (107-21-1)

Log Pow -1.36

12.4. Mobility in soil

No additional information available.

12.5. Results of PBT and vPvB assessment

Antifreeze/Coolant Super Plus Premium

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII.

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.

12.6. Other adverse effects

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product.

13. SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Dispose of in accordance with local regulations.

Waste treatment methods Collect and reclaim or dispose in closed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with licensed collector's sorting instructions.

Product/Packaging disposal recommendations Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken for recycling, recovery or waste in accordance with local regulation.

European List of Waste (LoW) code

The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.

16 01 14* antifreeze fluids containing dangerous substances

15 01 10* packaging containing residues of or contaminated by dangerous substances

14. SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

Not regulated for transport

15. SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006

Ethandiol 3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008

Antifreeze/Coolant Super Plus Premium - Ethandiol - Sodium 2-ethylhexanoate 3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC (EU)

0 %

Other information, restriction and prohibition regulations

Directive 94/33/EC on the protection of young people at work, as amended. For details, refer to section 3 and 8.

Seveso Information

Not applicable

National regulations

No additional information available.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

16. SECTION 16: Other information

Abbreviations and acronyms

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE	Acute Toxicity Estimate.
BCF	Bioconcentration factor.
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008.
DMEL	Derived Minimal Effect level.
DNEL	Derived-No Effect Level.
DPD	Dangerous Preparations Directive 1999/45/EC.
EC50	Median effective concentration.
IARC	International Agency for Research on Cancer.
IATA	International Air Transport Association.
IMDG	International Maritime Dangerous Goods.
LC50	Median lethal concentration.
LD50	Median lethal dose.
LOAEL	Lowest Observed Adverse Effect Level.
NOAEC	No-Observed Adverse Effect Concentration.
NOAEL	No-Observed Adverse Effect Level.
NOEC	No-Observed Effect Concentration.
OECD	Organisation for Economic Co-operation and Development.
PBT	Persistent Bioaccumulative Toxic.
PNEC	Predicted No-Effect Concentration.
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail.
SDS	Safety Data Sheet.
STP	Sewage treatment plant.
TLM	Median Tolerance Limit.
vPvB	Very Persistent and Very Bioaccumulative.
OEL	Occupational Exposure Limit.
RRN	REACH Registration no..

TWA	Time Weighted Average. The average concentration of a chemical in air over the total exposure time-usually an 8-hour workday..
VOC	Volatile organic compounds.
STEL	Short-term Exposure Limit.

Data sources REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006..

Full text of H- and EUH-statements

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4.
Repr. 2	Reproductive toxicity, Category 2.
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2.
H302	Harmful if swallowed.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Acute Tox. 4 (Oral)	H302	Calculation method
STOT RE 2	H373	Calculation method

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Attachment to the Safety Data Sheet



Product Name: Antifreeze/Coolant Super Plus Premium
Ford Int. Ref. No.: 194810

Page: 1/1
Print Date: 23.10.2018

Involved Products:

	Finiscode	Part number	Container Size:
1.	1 931 970	FU2J 19544 CA	20 l
2.	1 931 957	FU7J 19544 AB	1 l
3.	2 361 569	FU7J 19544 AD	1 l
4.	1 931 961	FU7J 19544 BB	5 l
5.	2 361 571	FU7J 19544 BD	5 l
6.	1 931 964	FU7J 19544 DA	60 l
7.	1 931 966	FU7J 19544 EA	200 l