



PLATINUM AGRO UTTO 10W-30

Quality class: API: GL-4
Conforms to ISO HV, DIN HVLP
Viscosity grad: SAE: 10W-30

GENERAL FEATURES:

Multipurpose multigrade transmission and hydraulic UTTO oil (Universal Tractor Transmission Oil). Ideal oil properties ensure trouble-free operation of hydraulic systems and transmissions in various types of agricultural machinery. Guarantee:

- excellent lubricating and anti-wear properties;
- good compatibility with sealing materials;
- dampening system vibrations;
- high resistance to oxidation

APPLICATION:

Platinum Agro UTTO 10W-30 oil recommended for lubrication of various types of gears (gear boxes, main gears, steering gears, differentials) and hydraulic systems installed in machines of various manufacturers. Suitable for tractors where manual transmission, axles, hydraulic fittings and "wet brakes" are lubricated by one oil system.

STANDARDS, APPROVALS. SPECIFICATION:

Suitable for use in tractors conforming to the following specifications:

John Deere JDM J20C
Massey Ferguson CMS M1135, M1141, M1143
White Farm (AGCO) Q-186
Ford ESN M2C86-B, M2C86-C
Case New Holland MAT3525 (FNHA-2-C-201.00, M2C 134D)
Case New Holland MAT 3540
Case New Holland MAT 3505 (MS1209)
Case MS 1206, 1207
Same
Landini
Deutz-Fahr
Claas (except for Renault transmission)
Fendt (except for Vario transmission)
Komatsu
Kubota UDT
ZF TE-ML 03E, 05F, 17E
Parker Denison UTTO/THF (tested on T6H20C, T5D, P46 pumps)
Vickers 35VQ25



RECOMMENDATIONS, REFERENCES Farmtrac

PARAMETERS	UNIT	TYPICAL VALUES
SAE viscosity grade	-	10W-30
Kinematic viscosity at. 100°C	mm ² /s	11,2
Viscosity index		130
Flow temperature	°C	-37
Flash point	°C	200

NOTE:
Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each product lot.

