



PLATINUM CLASSIC DIESEL SEMISYNTETYCZNY 10W-40

Quality class: API: CF
Viscosity grad: SAE:10W-40

GENERAL FEATURES:

Semi-synthetic engine oil for Diesel engines. The perfect composition of base oils and specially selected package of enriching additives ensures optimum engine protection both in summer and winter, ensures optimal engine lubrication and protection from a very start.

It guarantees:

- high performance in a wide range of operating conditions
- balanced engine operation even under heavy loads and in extreme conditions
- excellent resistance to oxidation and thermal stability
- long-lasting engine protection against deposits
- perfect acid neutralisation

APPLICATION:

Platinum Classic Diesel Semisynthetic 10W-40 – thanks to excellent oil composition, it can be used both in mild and extreme driving conditions. Designed especially for Diesel engines. Excellent performance both in passenger cars and light commercial vehicles with or without turbochargers. High quality oil components ensure high engine performance on different routes during year-long operation. Ideal for use in place of synthetic oils for cars with a few year-long mileage.

STANDARDS, APPROVALS. SPECIFICATION:

Meets the requirements of:
Mercedes – Benz 229.1



Physical and chemical properties:

PARAMETERS	UNIT	TYPICAL VALUES
Viscosity class SAE	-	10W-40
Kinematic viscosity in temp. 100°C	mm ² /s	14,5
Viscosity index	-	156
Pour point	°C	-32
Flash point	°C	233
Total Basic Number (TBN)	mg KOH/g	8,5

NOTE:

Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each product lot.

