



PLATINUM CLASSIC GAS MINERAL 15W-40

Quality class: API: SL
Viscosity grad: SAE: 15W-40

GENERAL FEATURES:

Mineral multi-grade motor oil, intended for the users of cars equipped with the LPG fuel installation. Excellent harmony of selected oil components ensures safe operation of the engine in all driving conditions.

It guarantees:

- Perfectly clean engine
- Effective and efficient lubrication even in heavy load conditions
- Excellent heat abstraction from the system
- effective and efficient sealing of piston - piston rings - cylinder sleeve system
- anticorrosion protection

APPLICATION:

Platinum Classic Gas Mineral 15W-40 is designed for year-long operation of engines in which the manufacturer recommends the use of oil with API SL quality category. Perfect for both passenger cars and light trucks operating with a dual-fuel system. Recommended for few-year-old and older vehicles equipped with first and second generation gas installations.

The oil proves itself in all driving conditions, not only on the motorways, but also in a regular urban traffic conditions.

PARAMETERS	UNIT	TYPICAL VALUES
Viscosity class SAE	-	15W-40
Kinematic viscosity in temp. 100°C	mm ² /s	14,1
Viscosity index	-	142
Pour point	°C	-32
Ignition temperature	°C	237
Total Basic Number (TBN)	mg KOH/g	8,5

NOTE:

Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each product lot.

