



PLATINUM ULTOR DIESEL 15W-40

Quality class: API: CF-4/ CF/ SJ
Viscosity grad: SAE: 15W-40

GENERAL FEATURES:

High quality oil designed primarily for use in diesel engines of trucks, buses and heavy equipment in different temperature conditions.

It guarantees:

- Engine protection against wear in extremely difficult conditions,
- Keeping the engine clean by preventing deposits formation,
- High lubricating properties even at the start of the engine.

APPLICATION:

Multigrade oil Platinum Ultor Diesel 15W-40 is designed for all types of diesel engines, turbocharged and normally aspirated, working in diverse conditions. Especially recommended for applications in trucks, buses and construction equipment. It is suitable for use in engines that meet Euro II.

STANDARDS, APPROVALS. SPECIFICATION:

Meets requirements:
MERCEDES-BENZ 228.0
MERCEDES-BENZ 228.1
MAN 270
MAN 271
MTU 1.0
DEUTZ DQC-I-05

Physical and chemical properties:

PARAMETERS	UNIT	TYPICAL VALUES
Flash point	°C	222
Viscosity grade SAE	-	15W-40
Kinematic viscosity at temp. 100°C	mm ² /s	13,0
Viscosity index	-	129
Pour point	°C	-33
TBN	Mg KOH/g	7,7
Sulphated ash	%	1,0

NOTE:
Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each product lot.

