


## PROFESSIONAL STARTERcable 900A

**Up to 900A peak amps**

For transferring the charging current to start even almost completely discharged batteries

**Up to 7 liters**

Suitable for starting vehicles with a petrol or diesel engine with a capacity of up to 7.0L

**450A Continuous amp rating**

For permanent current transmission and protection against overheating, a continuous amp rating of 450A is given

**Pure Copper**

The cable consists of multi-stranded conductors made of pure copper

**Professional starter cables from OSRAM**

With a range of OSRAM starter cables, motorcycle, car, commercial vehicle and truck drivers now have a quick and easy solution to rapidly transfer the battery power between a donor and a receiver vehicle and thus become ready to drive again. The OSRAM BATTERYstart PROFESSIONAL STARTER CABLE 900A is a high quality starter cable designed for professional and private use. The cables consist of multi-stranded conductors made of pure copper, which makes the resistance of the cable extremely low and enables a constant and effective transmission of the charge. The OSRAM BATTERYstart PROFESSIONAL STARTER CABLE 900A offers a high level of application safety thanks to the TÜV/GS-tested quality and is additionally CE-certified. The starter cable has a length of 4.5 meters with a cross-sectional area of 35mm<sup>2</sup>. Thanks to the length and the cross-sectional area, it is possible to start vehicles with petrol and diesel engines with up to 7.0 liters of displacement, as a peak current strength of up to 900A can be achieved, at the same time a continuous amp rating of 450A is given. It is suitable for voltages of 12V and 24V. To prevent high wear and tear, the OSRAM BATTERYstart STARTER CABLE 900A is sheathed in flexible yet durable PVC, the insulated clamps and handles provide additional safety and durability. The different colors of the cables and the handles on the clamps reduce the risk of mixing up the positive and negative terminals and thus the risk of incorrect connection to the battery. The storage bag included in the scope of delivery allows the cables to be stored tidy and, in a space-saving manner. Conveniently, the operating instructions are also attached to the back of the storage bag and are thus quickly at hand. OSRAM offers a 2-year guarantee\* on this product.

## Karta katalogowa produktu

### Dane techniczne


#### Informacje o produkcie

Engine type	Diesel / Petrol
-------------	-----------------

#### Dane elektryczne

Prąd szczytowy (A)	900A
Continuous amp rating	450 A

#### Wymiary i waga



Długość	345 mm
Szerokość	225 mm
Wysokość	85 mm
Długość przewodów	4,5m
Cross section area	35 mm <sup>2</sup>
Engine size	≤ 7.0L

#### Kolory i materiały

Material	Copper
----------	--------

#### Environmental information

<b>Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)</b>	
Date of Declaration	28-02-2022
Primary Article Identifier	4062172220934
Declaration No. in SCIP database	In work

### Dane logistyczne

## Karta katalogowa produktu

Kod produktu	Opis produktu	Opakowanie (liczba produktów / opakowanie)	Wymiary (długość x szerokość x wysokość)	Objętość	Waga brutto
4062172220934	STARTERcable 900A	Torebka 1	250 mm x 250 mm x 60 mm	3.75 dm <sup>3</sup>	19035.00 g
4062172220941	STARTERcable 900A	Karton wysylkowy 4	270 mm x 230 mm x 270 mm	16.77 dm <sup>3</sup>	19389.00 g

Wymieniony kod produktu oznacza najmniejszą ilość produktu, jaka może być zamówiona. Jednostka transportowa może zawierać jedną sztukę lub więcej. Składając zamówienie prosimy o zamawianie ilości odpowiadających jednej lub wielokrotności jednostki transportowej.

### Informacje prawne

\*szczegółowe informacje na temat gwarancji:

[www.osram.pl/am-gwarancje](http://www.osram.pl/am-gwarancje)

Application advice: For more detailed application information and graphics please see product datasheet and user manual.

### Wskazówki dotyczące zastosowania

Więcej szczegółowych informacji dotyczących grafik i zastosowania znajduje się w karcie katalogowej produktu

### Oświadczenie

Zastrzega się możliwość zmian bez uprzedzenia. Błędy i ominięcia są możliwe. Należy zawsze upewnić się czy korzystasz z najnowszej wersji katalogu.

# OSRAM