



RAVENOL ATF Type Z1 Fluid



FABRICATION SYNTHETIC

RECOMMENDATIONS HONDA 08266-99904 | HONDA 08266-99907 |
HONDA 08200-9005

RAVENOL ATF Type Z1 Fluid is synthetic ATF (Automatic Transmission Fluid) based on of high-quality hydrocrack oils with special additives and inhibition which guarantee a perfect function of the automatic transmission.

ART.-NR. 1211109

1 L | 1211109-001
4 L | 1211109-004
10 L | 1211109-010
20 L | 1211109-020
20 L | 1211109-B20
60 L | 1211109-060
60 L | 1211109-D60
208 L | 1211109-208
208 L | 1211109-D28
1000 L | 1211109-700

RAVENOL ATF Type Z1 Fluid is ATF (Automatic Transmission Fluid) of latest generation for all 4- and 5-stroke transmission of Honda. It guarantees in any mode for maximum wear protection.

RAVENOL ATF Type Z1 Fluid is red coloured.

Application Notes

RAVENOL ATF Type Z1 Fluid was developed for the use in automatic transmissions especially for Honda (BMXA, SLXA, SPCA, BDRA, SMLA, SDMA, MZHA, MZJA, MKZA, GPPA, BAYA, MAYA, SMMA u.a.).

Maintenance-filling under normal operating conditions.

Characteristics

RAVENOL ATF Type Z1 Fluid offers:

- Very good lubricating ability even at low temperatures in winter
- A high, stable viscosity index
- Very good oxidation stability
- Protection against corrosion and foam formation
- Good balanced coefficient of friction
- A high thermal and oxidative stability
- An excellent cooling capacity.

RAVENOL special transmission fluid is special development for special gear and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data. Please note: RAVENOL special transmission fluid is exclusively to apply under the original number, as indicated in the



product information. Not sure of the correct transmission fluid, you can ask your garage or the car dealer with respect to the original OEM gear type and number or consult our advisers. It must be specified the VIN code (Vehicle Identification Number) of your vehicle. Misapplication of RAVENOL special transmission fluid can lead to malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. cause and cause the failure of the transmission. Ravensberger Schmierstoffvertrieb GmbH does not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.



Property	Unit	Data	Audit
Density at 20°C	kg/m ³	838,0	EN ISO 12185
Colour		rot	visual
Pourpoint	°C	-54	DIN ISO 3016

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 22. August 2019