



## RAVENOL DW-1 Fluid



**FABRICATION SYNTHETIC**

**RECOMMENDATIONS** HONDA 08200-9009 | HONDA 08200-9008 | HONDA 08266-99964 | HONDA 08266-99967 | HONDA 08266-99901

**RAVENOL DW-1 Fluid** is a synthetic ATF (Automatic Transmission Fluid), designed on the basis of high quality hydrocrack oils with a special additive and inhibition, which ensure a perfect function of the automatic transmission.

### ART.-NR. 1211125

1 L	1211125-001
4 L	1211125-004
10 L	1211125-010
20 L	1211125-020
20 L	1211125-B20
60 L	1211125-060
60 L	1211125-D60
208 L	1211125-208
208 L	1211125-D28
1000 L	1211125-700

Due to its special formulation the properties of **RAVENOL DW-1 Fluid** are crucial. We assure an excellent cold stability.

## Application Notes

**RAVENOL DW-1 Fluid** is specially designed for use in the latest automatic transmissions of Honda.

Please note: Follow manufacturer's original equipment number!

## Characteristics

**RAVENOL DW-1 Fluid** offers:

- Extremely low pour Point
- Improved viscosity and coefficient of friction behaviour
- A very good protection against consumption
- Excellent thermal stability
- Improved EP-characteristics
- A good foaming behaviour
- Neutral behaviour towards sealing materials
- Reliable protection against corrosion

RAVENOL special transmission fluid is special development for special gear and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the



decision was made not to give technical data. Please note: RAVENOL special transmission fluid is exclusively to apply under the original number, as indicated in the product information. Not sure of the correct transmission fluid, you can ask your garage or the car dealer with respect to the original OEM gear type and number or consult our advisers. It must be specified the VIN code (Vehicle Identification Number) of your vehicle. Misapplication of RAVENOL special transmission fluid can lead to malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. cause and cause the failure of the transmission. Ravensberger Schmierstoffvertrieb GmbH does not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.



Property	Unit	Data	Audit
Density at 20°C	kg/m <sup>3</sup>	838,0	EN ISO 12185
Colour		rot	visual
Pourpoint	°C	-54	DIN ISO 3016

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 30. October 2019