



## RAVENOL SSG Spec Synt LKW Getriebeöl 75W-80



**VISCOSITY** 75W-80

**SPECIFICATIONS** API GL-4 | MIL-L-2105

**FABRICATION** SYNTHETIC

**APPROVALS** MAN 341 Z4 | ZF TE-ML 01L | ZF TE-ML 02L | ZF TE-ML 16K (ZF003704)

**RECOMMENDATIONS** MAN 341 VR | MAN 341 E3 | DAF/VOLVO 97305 | DAF/VOLVO 97307 | EATON (EXTENDED DRAIN) | RENAULT | IVECO

### ART.-NR. 1221100

1 L	1221100-001
4 L	1221100-004
10 L	1221100-010
20 L	1221100-020
20 L	1221100-B20
60 L	1221100-060
60 L	1221100-D60
208 L	1221100-208
208 L	1221100-D28
1000 L	1221100-700

**RAVENOL SSG Spec Synt Getriebeöl 75W-80** is a synthetic low viscosity transmission oil specifically for highly stressed manual transmissions.

**RAVENOL SSG Spec Synt Getriebeöl 75W-80** is designed based on synthetic base oils and specially coordinated additive treatment. This exceeds the needs of today's application requirements.

**RAVENOL SSG Spec Synt Getriebeöl 75W-80** is outstanding for use under severe mechanical and thermal stress on transmission oils, even with extended oil change intervals.

## Application Notes

**RAVENOL SSG Spec Synt Getriebeöl 75W-80** is a heavy duty transmission oil to care for synchronised manual transmissions in commercial vehicles with interarder or retarder. Shift comfort is noticeably increased. Extreme oil change intervals according as specified by the manufacturer at up to 500,000 km reduce maintenance costs and increase cost-effectiveness.

## Characteristics

**RAVENOL SSG Spec Synt Getriebeöl 75W-80** offers:

- Excellent thermal stability.
- High protection from rust, corrosion, foaming.
- Low solidification point.
- Excellent EP properties.
- Good shifting behaviour in low temperatures.
- Extended life.
- Fuel savings.



Property	Unit	Data	Audit
Density at 20°C	kg/m <sup>3</sup>	855,0	EN ISO 12185
Colour		rot	visual
Viscosity at 100°C	mm <sup>2</sup> /s	9,5	DIN 51562-10
Viscosity at 40°C	mm <sup>2</sup> /s	55,15	DIN 51562-10
Viscosity index VI		156	DIN ISO 2909
Brookfield Viscosity	mPa*s	52.400	ASTM D 2983
Pourpoint	°C	-42	DIN ISO 3016
Flash point	°C	238	DIN ISO 2592
Copper Strip Test		1b	ASTM D130

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 07. April 2021