



1 L | 1211118-001  
4 L | 1211118-004  
10 L | 1211118-010  
20 L | 1211118-020  
20 L | 1211118-B20  
60 L | 1211118-060  
60 L | 1211118-D60  
208 L | 1211118-208  
208 L | 1211118-D28

## RAVENOL ATF JF405E

**Category** Gear oil for automatic transmissions

**Item number** 1211118

**Oil type** Synthetic

**Recommendation** Esso JWS3314, Hyundai 04500-00130, Hyundai 04500-00430, Hyundai 45000-34D00, Hyundai JWS3314, Suzuki 99000-22A80-025, Suzuki ATF 3314

**Application** Passenger car

**RAVENOL ATF JF405E** is a synthetic ATF (Automatic Transmission Fluid), designed on the basis of high quality hydrocrack oils with a special additive and inhibition, which ensure a perfect function of the automatic transmission.

**RAVENOL ATF JF405E** is an ATF (automatic transmission fluid) for modern 4-speed automatic transmission JF402E and JF405E of Jatco for Mazda AZ-Wagon, Spiano, KIA Picanto/Morning, Chevrolet Matiz, Opel Agila, Hyundai Atos, Suzuki Wagon-R, Cervo, Nissan Moco, Pino. Guarantees maximum wear protection in all operating conditions.

**RAVENOL ATF JF405E** is red colored.

### Application Note

**RAVENOL ATF JF405E** is for use in 4-Stroke automatic transmission JF405E or JF402E from Jatco for Hyundai SANTRO 1.1L, Hyundai Atoz, KIA MORNING 1.0L and 1.1L, KIA PICANTO 1.0L, KIA VISTO 0.8L, Nissan MARCH 1.0L, Nissan Moco, Nissan Pino, Opel Agila 1.0L, Suzuki Alto 0.7L, Suzuki Cervo 0.7L, Suzuki Cultus 1.3L, Suzuki Kei 0.7L, Suzuki Lapin 0.7L, Suzuki MR Wagon 0.7L, Suzuki Palette 0.7L, Suzuki Wagon R 0.7L, Daewoo Matiz, Mazda AZ-Wagon, Mazda Laputa.

### Characteristics

- a very good lubricating ability even at low temperatures in winter
- a high, stable viscosity index
- a very good oxidation stability
- as far as possible protection against corrosion and foam formation
- good balanced coefficient of friction
- a high thermal and oxidative stability
- a excellent cooling capacity

### Technical Product Data

Colour

rot

VISUELL

Pourpoint

-54

°C

DIN ISO 3016

26.11.2021