



FLUIDE ATX

AUTOMATIC TRANSMISSION FLUID

PERFORMANCES LEVELS

OEM-approved	Meets the requirements	Suitable for
✓ Mercedes-Benz MB-Approval 236.6	✓ Ford Mercon	✓ Allison C4
✓ MAN 339 Typ V1/Z1	✓ GM DEXRON® IID	✓ BMW: Group 23-3.0, 24-3.0
✓ VOITH H55.6335.xx		
✓ ZF TE-ML03D/ 04D/09/11A/14A/17C		
✓ PSA S71 2102		

APPLICATIONS

- Automatic or semi-automatic transmissions and torque converters of passenger cars, light commercial vehicles and industrial vehicles, when the manufacturer requires an ATF (Automatic Transmission Fluid) GM DEXRON® -IID. Not suitable when a fluid type FORD M2C-33F or G is required.
- Manual gear boxes when an ATF fluid is required.
- Hydrostatic transmissions.
- Power steering.
- Hydraulic systems when a fluid type GM DEXRON® -IID is required.

TOTAL LUBRIFIANTS – Immeuble Spazio
562, avenue du Parc de l'île
92029 Nanterre cedex
France

FLUIDE ATX

Update: 01/2020



This lubricant does not cause adverse health effects when used in the intended application. A safety datasheet, is accessible on request from your local dealer.

CUSTOMER BENEFITS

- Very high viscosity index linked with an **excellent viscosity stability** in operation.
- **Very low pour point.**
- **Very good thermal stability.**
- **Excellent resistance to oxidation.**
- **Friction properties** specific to the requirements of GENERAL MOTORS Hydramatic.
- **Viscosity adapted** to MERCEDES requirements MB-Approval 236.6.

PHYSICAL AND CHEMICAL CHARACTERISTICS

FLUIDE ATX	Unit	Method	Value
Colour	-	ASTM D1500	Red
Density at 15°C	kg/m ³	ASTM D4052	866,6
Kinematic Viscosity at 40 °C	mm ² /s	ASTM D445	40,5
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	8,08
Brookfield Viscosity at -40°C	cP	ASTM D2983	24500
Viscosity Index	-	ASTM D2270	183
Pour Point	°C	ASTM D97	-51
Flash Point	°C	ASTM D92	210

**The features mentioned above are average values obtained with some variability in production and do not constitute a specification.*

TOTAL LUBRIFIANTS – Immeuble Spazio
562, avenue du Parc de l'île
92029 Nanterre cedex
France

FLUIDE ATX
Update: 01/2020



This lubricant does not cause adverse health effects when used in the intended application. A safety datasheet, is accessible on request from your local dealer.

RECOMMENDATIONS FOR USE

Before using the product, it is important to check the service manual of the vehicle: the drain is carried out according to the manufacturer's requirements.

The product should not be stored at a temperature above 60 °C while avoiding exposure to strong sunlight, extreme cold or high temperature variations.

All packages should be protected from bad weather conditions. Otherwise, the drums should be stored horizontally to avoid a possible contamination by water and the damage of the product label.

HEALTH, SAFETY AND ENVIRONMENT

Based on available information, this product does not cause adverse health effects when used in the intended application and the recommendations provided in the Safety Data Sheet (MSDS) are followed. The information is accessible on request from your local dealer or on the website www.quickfds.com.

This product should not be used for applications other than those for which it is intended.

If disposing of used product, take care to protect the environment and comply with local regulations.

TOTAL LUBRIFIANTS – Immeuble Spazio
562, avenue du Parc de l'île
92029 Nanterre cedex
France

FLUIDE ATX

Update: 01/2020



This lubricant does not cause adverse health effects when used in the intended application. A safety datasheet, is accessible on request from your local dealer.