

TOTAL QUARTZ 9000 ENERGY 5W-40

Engine oil

KEY DATA

LIGHT VEHICLE RANGE



PETROL & DIESEL ENGINE LUBRICANT
SAE 5W-40
SYNTHETIC TECHNOLOGY



INTERNATIONAL STANDARDS

- ACEA A3/B4
- API SN/CF

MANUFACTURER SPECIFICATIONS¹

- **VOLKSWAGEN:** 502.00/505.00
- **BMW:** LL-01
- **MERCEDEZ-BENZ:** MB-Approval 229.5
- **PORSCHE:** A40
- Meets the requirements of Chrysler MS-12991
- Meets the requirements of FIAT 9.55535-M2

¹ Please refer to car owner's manual

TECHNOLOGY

Age-Resistance technology

The next gen oil for outstanding protection.

Age-Resistance technology provides expert protection, to fight everyday challenges in the long term.

Age-Resistance technology offers unbeatable engine protection. It's unique combination of hyperactive molecules creates a strong thick oil film on all concerned engine parts. Engines are absolutely protected against a variety of challenges, from wear to oil oxidation even at extreme temperatures.



APPLICATIONS

TOTAL QUARTZ 9000 ENERGY 5W-40 is synthetic technology engine oil that has been developed to cover the most stringent requirements of both gasoline and diesel passengers car engines. TOTAL QUARTZ 9000 ENERGY 5W-40 is particularly suitable for turbo-compressed, multi-valve and direct injection diesel engines.

This engine oil can be used in the most difficult operating conditions (motorways, dense city traffic...), and is appropriate for all driving types, in particular for sporting or intense drive, and for every season.

TOTAL QUARTZ 9000 5W-40 is perfectly suited to engines with catalytic converters and all engines using lead-free fuel or LPG

CUSTOMERS BENEFITS

- **Anti-wear protection:** Ensures optimum engine longevity with its anti-wear properties that protect engine's most sensitive parts.
- **Oxidation resistance:** This lubricant allows extra long drain intervals.
- **All driving conditions:** Good fluidity at low temperatures for facilitating cold starts, resistant even at the highest temperatures.
- **Optimum engine protection:** Immediate lubrication of all engine components at start-up, even the most fragile.
- **Engine cleanliness:** Detergent and specific dispersive additives.

CHARACTERISTICS

TEST	UNIT	TEST METHOD	RESULT
Viscosity grade	-	SAE J300	5w-40
Kinematic viscosity at 40°C	mm ² /s	ASTM D445	90
Kinematic viscosity at 100°C	mm ² /s	ASTM D445	14.7
Viscosity Index	-	-	172
Flashpoint	°C	ASTM D92	232
Pour point	°C	ASTM D97	-36
Density	Kg/m ³	ASTM D1298	855

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off..

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet. This can be obtained on request from your local reseller and is available for consultation at www.quickfds.fr.

This product should not be used for any purposes other than the ones for which it is intended.

TOTAL LUBRIFIANTS – Immeuble Spazio
562, avenue du Parc de l'île
92029 Nanterre cedex
France

TOTAL QUARTZ 9000 ENERGY 5W-40
Last update of this datasheet: 03/2020

Some variations can be expected under normal production conditions, but these should not affect the product's expected performance irrespective of the site. The information contained in this document is subject to change without notice. Our products can be viewed on our website at www.lubricants.total.com