

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SDS #: 35940 QUARTZ INEO MC3 5W-30

Date of the previous version: 2018-02-01 Revision Date: 2018-04-23 Version 4.09

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE

COMPANY/UNDERTAKING

1.1. Product identifier

Product name QUARTZ INEO MC3 5W-30

Number LKY Substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Motor oil.

1.3. Details of the supplier of the safety data sheet

Supplier A - TOTAL UK LIMITED

183 Eversholt St, Kings Cross

London, NW1 1BU UNITED KINGDOM Tel: +44 (0)20 7339 8000 Fax: +44 (0)20 7339 8033

B - TOTAL LUBRIFIANTS 562 Avenue du Parc de L'ile

92029 Nanterre Cedex

FRANCE

Tél: +33 (0)1 41 35 40 00 Fax: +33 (0)1 41 35 84 71***

For further information, please contact:

Contact Point A - HSE

B - HSE***

E-mail Address A - rm.gb-msds@total.co.uk

B - rm.msds-lubs@total.com***

1.4. Emergency telephone number

Emergency telephone: +44 1235 239670

UK: National Poisons Information Service (NPIS): NHS on 111 or a doctor

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture



Revision Date: 2018-04-23 Version 4.09

REGULATION (EC) No 1272/2008 ***

For the full text of the H-Statements mentioned in this Section, see Section 2.2.***

Classification

The product is not classified as dangerous according to Regulation (EC) No. 1272/2008***

2.2. Label elements

Labelled according to REGULATION (EC) No 1272/2008

Signal word

None***

Hazard Statements ***

None***

Precautionary statements

None***

Supplemental Hazard Statements

EUH210 - Safety data sheet available on request***

2.3. Other hazards

Physical-Chemical Properties Contaminated surfaces will be extremely slippery.

Environmental properties The product may form an oil film on the water surface that may stop the oxygen exchange.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixture

Chemical nature Mineral oil of petroleum origin.

Hazardous components

Chemical Name	EC-No	REACH Registration Number	CAS-No	Weight %	Classification (Reg. 1272/2008)
Distillates (petroleum), hydrotreated heavy paraffinic***	265-157-1***	01-2119484627-25	64742-54-7	40-<50	Asp. Tox. 1 (H304)
Distillates (petroleum), hydrotreated light paraffinic***	265-158-7***	01-2119487077-29	64742-55-8	5-<10	Asp. Tox. 1 (H304)
bis(nonylphenyl)amine***	253-249-4***	01-2119488911-28	36878-20-3	1-<2.5	Aquatic Chronic 4 (H413)
Tetrapropenyl phenol ***	310-154-3***	01-2119513207-49**	121158-58-5	0.025-<0.1	Skin Corr. 1C (H314) Eye Dam. 1 (H318) Repr. 1B (H360F) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)



Revision Date: 2018-04-23 Version 4.09

Acute M factor 10
Chronic M factor 10***

Additional information Product containing mineral oil with less than 3% DMSO extract as measured by IP 346.

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

General advice IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR

EMERGENCY MEDICAL CARE.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. Wash contaminated clothing before reuse.

Inhalation Remove casualty to fresh air and keep at rest in a position comfortable for breathing. If not

breathing, give artificial respiration.

Ingestion Clean mouth with water. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician or poison control centre immediately.

Protection of first-aiders First aider needs to protect himself. See Section 8 for more detail. Do not use

mouth-to-mouth method if victim ingested or inhaled the substance; induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper

respiratory medical device.

4.2. Most important symptoms and effects, both acute and delayed

Eye contact Not classified based on available data.

Skin contact Not classified based on available data.

InhalationNot classified based on available data. Inhalation of vapours in high concentration may

cause irritation of respiratory system.

Ingestion Not classified based on available data. Ingestion may cause gastrointestinal irritation,

nausea, vomiting and diarrhoea.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to physician Treat symptomatically.

Section 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media Carbon dioxide (CO₂). ABC powder. Foam. Water spray or fog.



SDS #: 35940

QUARTZ INEO MC3 5W-30

Revision Date: 2018-04-23 Version 4.09

Unsuitable Extinguishing MediaDo not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Special hazard Incomplete combustion and thermolysis may produce gases of varying toxicity such as

carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration. Combustion products include sulphur oxides (SO2 and SO3) and Hydrogen sulphide H2S. Mercaptans.

Nitrogen oxides (NOx). Phosphorous oxides. Zinc oxides.

5.3. Precautions for fire-fighters

Special protective equipment for

fire-fighters

Wear self-contained breathing apparatus and protective suit.***

Other information Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing

water must be disposed of in accordance with local regulations.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

General Information Do not touch or walk through spilled material. Contaminated surfaces will be extremely

slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all

sources of ignition.

6.2. Environmental precautions

General Information Do not allow material to contaminate ground water system. Prevent entry into waterways,

sewers, basements or confined areas. Local authorities should be advised if significant

spillages cannot be contained.

6.3. Methods and material for containment and cleaning up

Methods for containment Dike to collect large liquid spills. If necessary dike the product with dry earth, sand or similar

non-combustible materials.

Methods for cleaning up Dispose of contents/container in accordance with local regulation. In case of soil

contamination, remove contaminated soil for remediation or disposal, in accordance with

local regulations.

6.4. Reference to other sections

Personal protective equipment See Section 8 for more detail.

Waste treatment See section 13.

Section 7: HANDLING AND STORAGE



Revision Date: 2018-04-23 **Version** 4.09

7.1. Precautions for safe handling

Advice on safe handling For personal protection see section 8. Use only in well-ventilated areas. Do not breathe

vapours or spray mist. Avoid contact with skin, eyes and clothing.

Prevention of fire and explosion Take precautionary measures against static discharges.

Hygiene measures Ensure the application of strict rules of hygiene by the personnel exposed to the risk of

contact with the product. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Regular cleaning of equipment, work area and clothing is recommended. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product

contaminated rags into workwear pockets.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures/Storage

conditions

Keep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep container tightly closed. Preferably keep in the original container. Otherwise, reproduce all the statutory information from the labels onto the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Store at room temperature. Protect from moisture.

Materials to avoid Strong oxidising agents.

7.3. Specific use(s)

Specific use(s) Please refer to Technical Data Sheet for further information.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parametres

Exposure limits Mineral oil mist:

USA: OSHA (PEL) TWA 5 mg/m3, NIOSH (REL) TWA 5 mg/m3, STEL 10 mg/m3, ACGIH

(TLV) TWA 5 mg/m³ (highly refined)

Legend See section 16

Derived No Effect Level (DNEL)

DNEL Worker (Industrial/Professional)

Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Distillates (petroleum), hydrotreated heavy paraffinic*** 64742-54-7				5.4 mg/m³/8h (aerosol - inhalation)
Distillates (petroleum), hydrotreated light				5.4 mg/m³/8h (aerosol - inhalation)



Revision Date: 2018-04-23 Version 4.09

paraffinic*** 64742-55-8			
bis(nonylphenyl)amine***		0.62 mg/kg bw/day	
36878-20-3		Dermal	
		4.37 mg/m3 Inhalation	
Tetrapropenyl phenol ***	166 mg/kg bw/day	0.25 mg/kg bw/day	
121158-58-5	Dermal	Dermal	
	44.18 mg/m3 Inhalation***	1.7621 mg/m³	
		Inhalation***	

DNEL Consumer

Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Distillates (petroleum),				1.2 mg/m ³ /24h (aerosol -
hydrotreated heavy				inhalation)
paraffinic***				
64742-54-7				
Distillates (petroleum),				1.2 mg/m³/24h (aerosol -
hydrotreated light				inhalation)
paraffinic***				
64742-55-8				
bis(nonylphenyl)amine***			0.31 mg/kg bw/day	
36878-20-3			Dermal	
			1.09 mg/m3 Inhalation	
			0.31 mg/kg bw/day Oral	
Tetrapropenyl phenol ***	50 mg/kg bw/day Dermal		0.075 mg/kg bw/day	
121158-58-5	13.26 mg/m ³ Inhalation		Dermal	
	1.26 mg/kg bw/day		0.79 mg/m3 Inhalation	
	Oral***		0.075 mg/kg bw/day	
			Oral***	

Predicted No Effect Concentration (PNEC)

Chemical Name	Water	Sediment	Soil	Air	STP	Oral
bis(nonylphenyl)ami	0.1 mg/l fw	132000 mg/kg dw	263000 mg/kg dw		1 mg/l	
ne***	0.01 mg/l mw	fw				
36878-20-3	1 mg/l or	13200 mg/kg dw				
		mw				
Tetrapropenyl	0.000074 mg/l fw	0.226 mg/kg fw	0.118 mg/kg		100 mg/l***	4 mg/kg food***
phenol ***	0.0000074 mg/l	dw	dw***			
121158-58-5	mw	0.0266 mg/kg mw				
	0.00037 mg/l	dw***				
	or***					

8.2. Exposure controls

Occupational Exposure Controls

Engineering measures

Apply technical measures to comply with the occupational exposure limits. Ensure adequate ventilation, especially in confined areas. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.

Personal protective equipment



> **Revision Date: 2018-04-23** Version 4.09

General Information Protective engineering solutions should be implemented and in use before personal

protective equipment is considered. The personal protective equipment (PPE) recommendations apply to the product AS DELIVERED. In case of mixtures or

formulations, it is suggested that you contact the relevant PPE suppliers.

None under normal use conditions. When workers are facing concentrations above the Respiratory protection

exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapour/particulate (EN 14387). Type A/P1. Warning! filters have a limited use duration. The use of breathing apparatus must comply strictly with the manufacturer's

instructions and the regulations governing their choices and uses.

If splashes are likely to occur, wear:. Safety glasses with side-shields. EN 166. Eye protection

Skin and body protection Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing. Type

4/6.

Hydrocarbon-proof gloves, Fluorinated rubber, Nitrile rubber, In case of prolonged contact Hand protection

with the product, it is recommended to wear gloves complying with EN 420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is

used, such as the danger of cuts, abrasion, and the contact time.

Not applicable

Environmental exposure controls

General Information The product should not be allowed to enter drains, water courses or the soil.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Clear **Appearance**

Colour yellow to amber

Physical state @20°C liquid

characteristic Odour

Odour Threshold No information available

Property Values Remarks Method

Melting point/range No information available

Boiling point/boiling range No information available

> 200 °C Cleveland Open Cup (COC) Flash point > 392 °F Cleveland Open Cup (COC)

No information available **Evapouration rate**



Revision Date: 2018-04-23 Version 4.09

Flammability Limits in Air

UpperNo information availableLowerNo information availableVapour pressureNo information availableVapour densityNo information available

Solubility in other solvents

logPow

No information available

No information available

No information available

No information available

Decomposition temperature

No information available

Viscosity, kinematic 69 mm2/s @ 40 °C ISO 3104

Explosive properties Not explosive Oxidising properties Not applicable

Possibility of hazardous reactions None under normal processing

9.2. Other information

Freezing point No information available

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

General Information None under normal processing.

10.2. Chemical stability

Stability Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Conditions to avoid Keep away from open flames, hot surfaces and sources of ignition. Keep away from heat

and sparks.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous Decomposition Products

Hazardous Decomposition Products Incomplete combustion and thermolysis may produce gases of varying toxicity such as

carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. Combustion products include sulphur oxides (SO2 and SO3) and Hydrogen sulphide H2S. Mercaptans.



SDS #: 35940

QUARTZ INEO MC3 5W-30

Revision Date: 2018-04-23 **Version** 4.09

Nitrogen oxides (NOx). Phosphorous oxides. Zinc oxides.

Section 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity Local effects Product Information

Skin contact . Not classified based on available data.

Eye contact . Not classified based on available data.

Inhalation . Not classified based on available data. Inhalation of vapours in high concentration may

cause irritation of respiratory system.

Ingestion . Not classified based on available data. Ingestion may cause gastrointestinal irritation,

nausea, vomiting and diarrhoea.

ATEmix (inhalation-dust/mist) 9.10*** mg/l*** mg/l

Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (petroleum), hydrotreated heavy paraffinic***	LD50 > 5000 mg/kg bw (rat - OECD 420)	LD50 > 5000 mg/kg bw (rabbit - OECD 402)	LC50 (4h) > 5 mg/l (aerosol) (rat - OECD 403)
Distillates (petroleum), hydrotreated light paraffinic***	LD50 > 5000 mg/kg bw (rat - OECD 420)	LD50 > 5000 mg/kg bw (rabbit - OECD 402)	LC50 (4h) > 5 mg/l (aerosol) (rat · OECD 403)
bis(nonylphenyl)amine***	LD50 > 5000 mg/kg (Rat - OECD 401)	LD50 > 2000 mg/kg (Rat - OECD 402)	
Tetrapropenyl phenol ***	LD50 2100-2200 mg/kg (Rat)***	LD50 15000 mg/kg (Rabbit)***	

Sensitisation

Sensitisation Not classified based on available data.

Specific effects

Carcinogenicity Not classified based on available data. During use in engines, contamination of oil with low

levels of combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil

is thoroughly removed by washing with soap and water.

Mutagenicity

Germ cell mutagenicity Not classified based on available data.

Reproductive toxicity Not classified based on available data. Contains toxic substance(s) listed as toxic to

reproduction.

Chemical Name	European Union
Tetrapropenyl phenol *** 121158-58-5	Repr. 1B (H360F)***

Repeated Dose Toxicity



> **Revision Date: 2018-04-23** Version 4.09

Target Organ Effects (STOT)

Specific target organ systemic toxicity (single exposure)

Not classified based on available data.

Specific target organ toxicity -

repeated exposure

Not classified based on available data.

Not classified based on available data. **Aspiration toxicity**

Other information

Other adverse effects Characteristic skin lesions (oil blisters) may develop following prolonged and repeated

exposures (contact with contaminated clothing).

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Not classified based on available data. This product contains one or more components that have a branched alkylphenol impurity which is very toxic to aquatic life (disclosed in section 3). Components containing the impurity have been tested and are not toxic to aquatic life. Therefore, the data in Section 3 for the alkylphenol impurity should not be used to classify the product for aquatic toxicity.

Acute aquatic toxicity - Product Information

No information available.

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates.	Toxicity to fish	Toxicity to microorganisms
Distillates (petroleum), hydrotreated heavy paraffinic*** 64742-54-7	EL50 (48h) > 100 mg/l (Pseudokirchnerella subcapitata - OECD 201)	EL50 (48h) > 10000 mg/l (Daphnia magna - OECD 202)	LL50 (96h) > 100 mg/l (Oncorhynchus mykiss - OECD 203)	
Distillates (petroleum), hydrotreated light paraffinic*** 64742-55-8	EL50 (72h) > 100 mg/l (Pseudokirchneriella subcapitata - OCDE 201)	EL50 (48h) > 10000 mg/L (Daphnia magna - OCDE 202)	LL50 (96h) > 100 mg/L (Oncorhynchus mykiss - OCDE 203)	
bis(nonylphenyl)amine*** 36878-20-3	EC50 (72h) > 100 mg/l (Desmodesmus subspicatus - OECD 201)	EC50 (48h) > 100 mg/l (Daphnia magna - OECD 202)	LC50 (96h) > 100 mg/l (Brachyanio rerio - OECD 203)	
Tetrapropenyl phenol *** 121158-58-5	EbC50 (72h) 0.15 mg/l (Scenedesmus subspicatus - OECD 201)***	EC50(48h) 0.037 mg/l (Daphnia magna - static - OECD 202)***	EL50(96h) 40 mg/l Pimephales promelas semi-static (OECD 203)***	

Chronic aquatic toxicity - Product Information

No information available.

Chronic aquatic toxicity - Component Information



Revision Date: 2018-04-23 Version 4.09

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates.	Toxicity to fish	Toxicity to microorganisms
Distillates (petroleum), hydrotreated heavy paraffinic*** 64742-54-7		NOEL (21d) 10 mg/l (Daphnia magna - QSAR Petrotox)	NOEL (14/28d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	
Distillates (petroleum), hydrotreated light paraffinic*** 64742-55-8		NOEL (21d) 10 mg/l (Daphnia magna - OCDE 211)	NOEL (14/28d) >1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	
Tetrapropenyl phenol *** 121158-58-5		NOEC(21d) 0.0037 mg/l (Daphnia magna - semi-static - OECD 211)***		

Effects on terrestrial organisms

No information available.

12.2. Persistence and Degradability

General Information

No information available.

12.3. Bioaccumulative potential

Product Information No information available.

logPow No information available

Component Information

Chemical Name	log Pow
Distillates (petroleum), hydrotreated heavy paraffinic*** - 64742-54-7	-
bis(nonylphenyl)amine*** - 36878-20-3	7.7
Tetrapropenyl phenol *** - 121158-58-5	7.14***

12.4. Mobility in soil

Soil Given its physical and chemical characteristics, the product generally shows low soil

mobility.

Air Loss by evaporation is limited.

Water The product is insoluble and floats on water.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment No information available.

12.6. Other adverse effects

General Information No information available.



Revision Date: 2018-04-23 Version 4.09

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from residues / unused

products

Should not be released into the environment. Do not empty into drains. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations. Where possible recycling is preferred to disposal or incineration.

Contaminated packageing

Empty containers should be taken to an approved waste handling site for recycling or

disposal.

EWC Waste Disposal No

According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used. The following Waste Codes are only suggestions:. 13 02

05.

Other information

Refer to section 8 for safety and protective measures for disposal personnel.

Section 14: TRANSPORT INFORMATION

ADR/RID not regulated

IMDG/IMO not regulated

ICAO/IATA not regulated

ADN not regulated

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Further information

No information available

15.2. Chemical Safety Assessment

Chemical Safety Assessment No information available



Revision Date: 2018-04-23 Version 4.09

15.3. National regulatory information

The United Kingdom

Avoid exceeding occupational exposure limits (see section 8).

Ireland

• Avoid exceeding occupational exposure limits (see section 8).

Section 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H304 - May be fatal if swallowed and enters airways

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H360F - May damage fertility

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

H413 - May cause long lasting harmful effects to aquatic life***

Abbreviations, acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

bw = body weight

bw/day = body weight/day

EC x = Effect Concentration associated with x% response

GLP = Good Laboratory Practice

IARC = International Agency for Research of Cancer

LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals

LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals LL = Lethal Loading

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

NOEL = No Observed Effect Level

OECD = Organization for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material

DNEL = Derived No Effect Level

PNEC = Predicted No Effect Concentration

dw = dry weight

fw = fresh water

mw = marine water

or = occasional release

Legend Section 8

TWA: Time Weight Average STEL: Short Time Exposure Limit



Revision Date: 2018-04-23 **Version** 4.09

+ Sensitiser * Skin designation
** Hazard Designation C: Carcinogen

M: Mutagen R: Toxic to reproduction

Revision Date: 2018-04-23

Revision Note *** Indicates updated section.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of Safety Data Sheet