



A brand of **TOTAL**

ELF RENAULTMATIC D2



Automatic Transmission and Power Steering Fluid

PERFORMANCES LEVELS

OEM-Approved

- ✓ Renault approval for power steering

Meets the requirements

- ✓ GM Dexron IID

APPLICATIONS

- Special fluid for automatic and hydrostatic transmission systems, recommended for all RENAULT cars and vans.
- Do not use ELF RENAULTMATIC D2 in automatic transmission and power-assisted steering systems of other brands of vehicle..

CUSTOMER BENEFITS

- **Fluid and viscous properties** adjusted for the coefficients of friction required for satisfactory clutch operation.
- **High viscosity number.**
- **Very low pour point.**
- Advanced **protection against wear, corrosion and foaming.**
- **Excellent thermal and chemical stability.**
- Very good **compatibility with seals.**
- Ensures **precision and flexibility of automatic sequences**, even at very low speeds and in any weather.



A brand of **TOTAL**

ELF RENAULTMATIC D2

PHYSICAL AND CHEMICAL CHARACTERISTICS

ELF RENAULTMATIC D2	Unit	Method	Value
Colour	-	ASTM D1500	Red
Density at 15°C	kg/m ³	ASTM D4052	867
Kinematic Viscosity at 40 °C	mm ² /s	ASTM D445	33,73
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	7,296
Viscosity Index	-	ASTM D2270	190
Pour Point	°C	ASTM D97	-51
Flash Point	°C	ASTM D92	208

**The features mentioned above are average values obtained with some variability in production and do not constitute a specification.*