



DYNATRANS MPV



TOTAL

Lubricant for **transmissions with oil immersed brakes** and hydraulic systems used in agricultural tractors and Public Works or handling equipment.

SPECIFICATIONS AND APPROVALS

International specifications

API GL-4

Manufacturer's approvals

- ✓ MASSEY F. CMS M1145/M1143
- ✓ VOLVO CE WB101
- ✓ ZF TE ML 03E/ 05F/ 06P/ 17E/ 21F

Suitable when the following specifications are recommended

- ✓ MASSEY F. CMS M1141/M1135
- ✓ JOHN DEERE JDM J20C
- ✓ CASE MS 1206 / 1207 / 1209
- ✓ NEW HOLLAND NH 410B / NH 410C
- ✓ CNH MAT 3505 / 3509 / 3525 / 3526 / 3540
- ✓ FORD M2C 134D / FNHA 2C 201.00
- ✓ KUBOTA UDT
- ✓ Mc CORMICK HTX
- ✓ AGCO/ Allis 821 XL
- ✓ CLAAS / RENAULT AGRICULTURE

APPLICATIONS

TOTAL DYNATRANS MPV has been especially developed for **transmissions with wet brakes** requiring an API GL-4 lubricant with a 10W-30 or 80W viscosity grade, in both Off-Road and On-Road vehicles.

This lubricant is also perfectly adapted to **automatic transmissions, torque converters and hydrostatic transmissions** and more generally to any transmissions requiring an **UTTO** (Universal Tractor Transmissions Oil) lubricant.

TOTAL DYNATRANS MPV is also designed to lubricate **hydraulic systems, power-assisted steering and power-take-offs (PTO) with wet clutches**.

PERFORMANCES AND CUSTOMER BENEFITS

TOTAL DYNATRANS MPV is adapted to a wide range of agricultural and Public Works equipment and helps to reduce the stock and the number of lubricants.

This lubricants shows **excellent low temperature performances** (protects friction brakes against sticking) and **high temperature performances** (protects against judder or excessive slip).

TOTAL DYNATRANS MPV has very good **extreme pressure and anti-wear properties** giving optimum protection of gears and hydraulic components.

PHYSICAL AND CHEMICAL CHARACTERISTICS*

TOTAL DYNATRANS MPV

		Method	Value
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	64
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	10.4
Viscosity Index	-	ASTM D2270	150
Pour Point	°C	ASTM D97	-39

* The features mentioned above are average values obtained with some variability in production and do not constitute a specification.

TOTAL LUBRIFIANTS

562, avenue du Parc de l'Île
92029 Nanterre cedex
FRANCE

TOTAL DYNATRANS MPV

Update 07/2015

www.lubricants.total.com



This lubricant does not cause adverse health effects when used in the intended application.
A safety datasheet is accessible on request from your local dealer or on the website www.quickfds.com