Product information Marine Multi-Spray

Phone: +49 (0)731/1420-13

e-mail: info@liqui-moly.de

Fax: +49 (0)731/1420-82

Service-hotline: 0800/8323230 Technical hotline: +49 (0)731/1420-871 www.liqui-moly.de

Description

Specifically designed for marine purposes to protect and preserve. Keeps moving parts moving and protects against corrosion and oxidation. Drives out moisture and protects the vessel's entire electrical system. Frees up bolts which have rusted solid and reduces squeaking noises. Neutral acting on plastics, paints, metals and wood.

Properties

- outstanding sea and salt water resistance
- penetrates and drives out moisture
- releases seized up and rusted on parts
- maintains components in electrical systems
- optimum penetration properties
- good corrosion protection
- environmentally friendly
- does not attack plastics, paints, metals and wood

Technical data

Form	flüssig / liquid
Base	Ölkombination / combination of oil
Color / appearance	gelblich-braun / yellowish-brown
Density at 20 °C	0,785 g/cm³
Odor	charakteristisch / characteristic
Flash point	-10 °C
Operating temperature range	-35 - +140 °C

Areas of application

Versatile product for use as a multi-purpose spray. For all maintenance and service work.

Application

LIQUIMOLY GmbH

89081 Ulm-Lehr

Jerg-Wieland-Str. 4

Spray the area to be treated and leave it to take effect.

		Prinigt + Schützt Pringt + Löst Cleans + Protects Preserves + Losse
		Made in Germany
05054		
25051		
D-F-I-E-GR		
DI I'L-OR		

GB-DK/N-FIN-S-RUS

Our information is based on thorough research and may be considered reliable, although not legally binding.

25052

Available pack sizes

400 ml Can aerosol

400 ml Can aerosol



