



Perfect for any maintenance or repair application, the 2130XP-K delivers plenty of power in a lightweight and ergonomic package.

- 816 Nm (602 ft-lb) of maximum torque in reverse.
- Ingersoll Rand TwinHammer impact mechanism is the strongest, most durable and longest life mechanism in the industry.
- Powerful reverse-bias 6-vane motor delivers even more power in reverse.
- Ergonomic composite housing is lightweight, protects from cold air and offers great operator comfort.
- Feather-touch trigger allows precise delivery of power and speed.
- 3-position power regulator in forward helps adjusting the power to the application.
- 360° swivel inlet helps eliminating twisted hoses.
- Silenced through-handle exhaust reduces the noise level.
- Kit contains:
 - Impactool™,
 - 1/2" impact socket set (10 pcs) (10, 11, 12, 13, 14, 17, 19, 21, 22 and 24 mm).

Specifications at 6.2 bar (90 psi)

Part Number	2130XP-K
Ordering number	16985301
Drive size (square)	1/2 in
Other available versions:	
- bare tool	2130XP
- kit with 3 long sockets	2130XP+SK4M3L

PERFORMANCE

Working torque in forward	25 - 350 ft-lb / 34 - 474 Nm
Maximum torque in reverse	602 ft-lb / 816 Nm
Recommended fastener size	9/16 in / M14
Free speed	9 500 rpm
Impacts per minute	1 200

AIR SYSTEM

Air Inlet (NPT)	1/4 in
Minimum hose size	3/8 in / 10 mm
Average air consumption	4.4 CFM / 125 L/min
Air consumption at load	22.0 CFM / 623 L/min

NOISE & VIBRATION

Impacting sound pressure / power (ISO15744)	94.3 / 105.3 dB(A)
Free speed sound pressure / power (ISO15744)	90.8 / 101.8 dB(A)
Vibration level / measurement uncertainty (ISO28927)	8.9 / 2.0 m/s ²

WEIGHT & DIMENSIONS

Tool weight	4.20 lb / 1.90 kg
Tool dimensions (L x W x H)	187 x 72 x 182 mm
Shipping weight	4.49 lb / 3.94 kg
Shipping dimensions (L x W x H)	343 x 320 x 108 mm
UPC / EAN code	6 63023 06533 5
Origin	Made in China




SK4M3L

81287377

1/2" Impact socket set (3 pcs) (17, 19 and 21 mm)


SK4M14

81287351

1/2" Impact socket set (14 pcs) (10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 23 and 24 mm)


Impact sockets

For the complete range, see our accessory catalogue.


2131-366

04706388

Horizontal hanger


2130-BOOT

45505369

Protective tool boot


33104

91486330

Hose whip, 1/4" NPT, 6 mm inside diameter, 30 cm (1 ft)


77NMC2

88104070

7N7/7S7 Series nipple, 1/4" male thread, 7.2 mm bore (EURO 7.2 - 7.4)


Filters, regulators, lubricators

For the complete range, see our accessory catalogue.


115-LBK1

04616108

Lubricant kit for Impacttools™ with composite housing


115-4T

04616157

Grease for Impacttools with composite housing


SK4M5L

81287369

1/2" Impact socket set (5 pcs) (17, 19, 21, 22 and 24 mm)


SK4M18

81287385

1/2" Impact socket set (18 pcs) (10, 11, 13, 14, 17, 19, 21, 22, 24, 13L, 14L, 21L, 24L, 17L, 19L and 21L mm, extension 125 mm)


4UA9

03070216

1/2" right-angle head (speed reduction: 25% torque output reduction: up to 50%)


BMDS-4

92842087

Cable balancer, 2-4 kg, 2 m (6-1/2 ft)


IB6NMC2

88103015

IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-C4109)


Quick Release Couplings

For the complete range, see our accessory catalogue.


10Z4

03875671

Oil, Class 1, no. 10, 0.12 L


Lubricants

For the complete range, see our accessory catalogue.