



The gold standard of the automotive service industry now delivers Extra Performance, as part of the exclusive new XP Series of tools. With increased durability, through-handle exhaust, quieter operation, improved throttle control and a countered rubber grip for superior comfort, the 231GXP is a **MUST** have for every automotive service industry professional!

- ◆ 610 Nm (450 ft-lb) of maximum torque in reverse.
- ◆ Through-handle exhaust directs air away from operator and work area.
- ◆ Variable power control, forward & reverse.
- ◆ Pressure feed system provides continuous lubrication.
- ◆ Twin-Hammer Plus impact mechanism with proprietary advanced metallurgy.

Specifications at 6.2 bar (90 PSI)

Part number	231GXP
Ordering number	10566255
Drive size (square)	1/2 in

PERFORMANCE

Working torque (forward)	25 - 300 ft-lb / 34 - 407 Nm
Working torque (reverse)	25 - 350 ft-lb / 34 - 475 Nm
Maximum torque (reverse)	450 ft-lb / 610 Nm
Recommended fastener size	9/16 in / M14
Maximum free speed	8 000 rpm
Impacts per minute	1 200

AIR SYSTEM

Air inlet (NPTF)	1/4 in
Minimum hose size	3/8 in / 10 mm
Average air consumption	4.2 cfm / 118 l/min
Air consumption at load	22 cfm / 616 l/min

NOISE & VIBRATIONS

Sound pressure / power	91.5 / 102.5 dB(A)
Vibration level (ISO8662)	4.7 m/s²

WEIGHT & DIMENSIONS

Tool weight	5.79 lb / 2.63 kg
Tool dimensions (l x w x h)	185 x 67 x 195 mm
Shipping weight	6.40 lb / 2.90 kg
Shipping dimensions (l x w x h)	240 x 215 x 83 mm
UPC/EAN Code	6 63023 01948 2

