

New



The 529 is a versatile air saw for cutting intricate shapes and light radius curves in all types of plastics, fiberglass and composite materials, as well as aluminum and sheet metal.

- Up to 9 500 blows per minute.
- Vibration reduction technology significantly increases user comfort and productivity.
- Rubber handle grip offers great operator comfort and protects from cold air.
- The small size of this tool will allow greater access to tight spaces.
- Integral trigger safety lock prevents accidental tool start.
- Rear exhaust directs air away from the operator.
- Tool delivered with blades.

Specifications at 6.2 bar (90 psi)

Part Number **529**
 Ordering number **47125885**

PERFORMANCE

Blade stroke **3/8 in / 10 mm**
 Blows per minute **9 500**

AIR SYSTEM

Air Inlet (NPT) **1/4 in**
 Minimum hose size **1/4 in / 6 mm**
 Average air consumption **1.10 CFM / 31 L/min**
 Air consumption at load **1.13 CFM / 32 L/min**

NOISE & VIBRATION

Sound pressure / power (ISO15744) **84.0 / 95.0 dB(A)**
 Vibration level / measurement uncertainty (ISO28927) **3.1 / 1.03 m/s²**

WEIGHT & DIMENSIONS

Tool weight **1.5 lb / 0.7 kg**
 Tool dimensions (L x W x H) **9.67 x 1.9 x 2.6 in / 246 x 48 x 67 mm**
 Shipping weight **1.87 lb / 0.85 kg**
 Shipping dimensions (L x W x H) **305 x 85 x 57 mm**
 UPC / EAN code **6 63023 09950 7**
 Origin **Made in Taiwan**





P4FS-6
45525474

Blades, 12 teeth per cm (6 pieces)



P4CS-6
45525508

Blades, 10 teeth per cm (6 pieces)



529-69
46816633

Wrench



IB6NMC2
88103015

IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-C4109)



77NMC2
88104070

7N7/7S7 Series nipple, 1/4" male thread, 7.2 mm bore (EURO 7.2 - 7.4)



Quick Release Couplings

For the complete range, see our accessory catalogue.



Filters, regulators, lubricators

For the complete range, see our accessory catalogue.



10Z4
03875671

Oil, Class 1, no. 10, 0.12 L



Lubricants

For the complete range, see our accessory catalogue.