

# AKROS TURBO 15W-40 Cod. 2255

## DESCRIPTION

Engine oil for high performance tractors and farm machines with turbocharged or aspirated engine of all types and power ratings.

## CHARACTERISTICS

Specifically formulated engine oil for the complete protection of tractors or other farm machines operating in the toughest conditions.

AKROS TURBO adds to the basic functions of AKROS engine oils:

- | High protection against the wear caused by the work of the machine under conditions with high load at low rpm.
- | Very good protection against deposits (sludge and other pollutants) Originated by high engine operating temperatures.
- | Excellent protection against acid products deriving from the combustion of fuel oils with high sulphur content.
- | Trouble-free cold starting along with high and constant pressure of the lubrication circuit under all operating conditions.



The specific features of a formula studied especially for supercharged engines in which the operating temperature and mechanical loads resulting from the high specific power rates require extra protection from the lubricant, in particular as far as the formation of deposits and wear are concerned.

It exceeds the quality specifications of the major european manufacturers.

## ADVICE ON USE

SAE 15W-40 allows trouble-free cold starting under all weather conditions for temperatures from -15°C to +40°C.

Drain interval:

according to the Manufacturer's instructions.

## TECHNICAL DATA

SAE 15W-40, SDFG OM-1991, ACEA E7/E5/E3, API CI-4/CH-4/CG-4/CF-4/CF, MB-Approval 228.3, CUMMINS CES 20078/20077/20076/20072/20071, CAT ECF-1, GLOBAL DHD-1, MAN M3275, VOLVO VDS-3, RENAULT RVI RLD-2 Performance, MACK EO-M Plus