



Fork Oil Factory Line

High performance Hydraulic Fluid for any telescopic fork

100% Synthetic

**4 Viscosities :
VERY LIGHT – LIGHT – LIGHT/MEDIUM –
MEDIUM**

TYPE OF USE

Hydraulic fluid for racing applications.

Specially formulated for SHOWA, KAYABA, OHLINS, WP forks, and any type of upside/down or conventional telescopic fork.

PERFORMANCE

Reduced internal friction, specially fork tubes and seals thanks to the exclusive anti-friction additive designed and developed by MOTUL.

Outstanding suspension performance as soon as riding and maintained performance in the time.

High performance anti-foam avoiding air transfer to the air chamber to maintain suspension performance.

Anti-wear and extreme pressure properties. Anti-corrosion. Seals protection.

RECOMMENDATIONS

MOTUL Fork Oil Factory Line can be mixed to obtain the required absorbing.

Use the exact quantity recommended by the fork manufacturer.

PROPERTIES

		VERY LIGHT 2.5W	LIGHT 5W	LIGHT MEDIUM 7.5W	MEDIUM 10W
Density at 20°C	ASTM D1298	0.834	0.834	0.835	0.835
Viscosity at 40°C	ASTM D445	15.0 mm ² /s	18.0 mm ² /s	24.0 mm ² /s	36.0 mm ² /s
Viscosity at 100°C	ASTM D445	3.5 mm ² /s	4.0 mm ² /s	4.9 mm ² /s	6.4 mm ² /s
Viscosity Index	ASTM D2270	112	121	131	130
Flash point	ASTM D92	205°C	208°C	230°C	244°C
Pour point	ASTM D97	<-39°C	<-39°C	<-36°C	<-39°C

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel : 33 1 48 11 70 00 - Fax : 33 1 48 33 28 79 - Web Site : www.motul.fr

09/10