



GARDEN 4T 10W-30

4 Stroke Engine Lubricant for Motorized Garden Tools

Gasoline and Diesel Engine

Technosynthese® - SAE 10W-30

TYPE OF USE

Specially formulated for motorized garden tools and small farming equipment.

All Gasoline and Diesel 4 stroke engines, naturally aspirated or turbocharged.

Lawn mowers, motor mowers, ride on mowers, tillers, light tractors,...

Suitable for all types of fuel: leaded and unleaded gasoline, Diesel fuel, Ethanol, biofuels.

All types of 4 stroke engines with or without catalytic converter.

PERFORMANCE

STANDARDS

API SJ - SH / CF

Technosynthese® lubricant reinforced with synthetic base stocks for improved engine protection

Ensures the engine cleanliness

Protection during wintering

Dispersant and detergent properties

Good cold starting, perfectly stable in a hot engine

Anti-wear, Anti-oxidation properties

Anti-corrosion, Anti-foam properties

RECOMMENDATIONS

Oil change: According to manufacturers' requirements and adjust according to your own use.

MOTUL GARDEN 4T SAE 10W-30 can be mixed with synthetic or mineral lubricants.

PROPERTIES

Viscosity grade	SAE J 300	10W-30
Density at 20°C (68°F)	ASTM D1298	0.872
Viscosity at 40°C (104°F)	ASTM D445	70.3 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	10.6 mm ² /s
Viscosity index	ASTM D2270	141
Flash point	ASTM D92	226°C / 439°F
Pour point	ASTM D97	-33°C / -27°F
TBN	ASTM D2896	10.3 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE.

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - Web Site: www.motul.com

03/16