



# TOP GREASE 200

**Multipurpose High Performance Grease**

**Lithium – Adherent**

**NLGI 2 – Extreme Pressure**

## TYPE OF USE

High performance multipurpose grease for roller bearings, articulations, bearings, hubs, universal joints, ball joint, cables,...etc. working under heavy loads and in humid conditions.  
Car, Motorbike, Marine, Transport, Civil Engineering machinery, Industry and Farm machines...

Temperatures for use : from -20°C / -4°F to +130°C / +266°F.

## PERFORMANCE

Multipurpose grease with lithium soap reinforced by adhesive polymers and with extreme-pressure, anti-wear, anti-oxidation and anti-corrosion additivation.

Excellent resistance to load thanks to its dedicated high performance extreme-pressure formula.

Excellent adherence of the grease and resistance to washing out thanks to the use of a sticky polymer.

Good properties at cold temperatures.

Good mechanical stability.

Designation DIN 51502 : KP 2 K-20

## PROPERTIES

Color	Visual	Orange
Consistency grade	DIN 51 818	NLGI 2
Soap		Lithium
Penetrability - 60 cycles	ASTM D217	265 / 295 x10 <sup>-1</sup> mm
Drop point	ASTM D2265	>190°C / >374°F
Anti-corrosion EMCOR	IP 220	0 / 0
TIMKEN Test - Load	ASTM D2509	45 lb
FAG FE-9 Test	DIN 51 821	F50 > 100 hr at 130°C (266 °F)

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL. 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 – Tel : 33 1 48 11 70 00 - FAX : 33 1 48 33 28 79 - Web Site: www.motul.fr

07/09