

# SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)



## SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product name : FUEL SYSTEM CLEAN MOTO  
Product code : 32201

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Additive

### 1.3. Details of the supplier of the safety data sheet

Registered company name : MOTUL  
Address : 119, Boulevard Felix Faure. 93300 AUBERVILLIERS CEDEX FRANCE  
Telephone : 33.1.48.11.70.00. Fax: 33.1.48.33.28.79. Telex: .  
Email : motul\_hse@motul.fr

### 1.4. Emergency telephone number : +44 (0) 1235 239 670.

Association/Organisation : ORFILA.

### Other emergency numbers

BRAZIL : +55 11 3197 5891 / COLOMBIA : +57 1 508 7337 / ARGENTINA : +54 11 5984 3690 / CHILE : +562 2582 9336  
Ireland : +353 1 8092566  
UNITED STATES: 001 866 928 0789 / CANADA: 001 800 579 7421 / MEXICO : +52 55 5004 8763 / MIDDLE EAST - AFRICA : +44 1235 239671  
24 hours a day, 7 days a week

## SECTION 2 : HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture


#### In compliance with EC regulation No. 1272/2008 and its amendments.

Flammable liquid, Category 2 (Flam. Liq. 2, H225).  
Acute inhalation toxicity, Category 4 (Acute Tox. 4, H332).  
Skin irritation, Category 2 (Skin Irrit. 2, H315).  
Serious eye damage, Category 1 (Eye Dam. 1, H318).  
Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H335).  
Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H336).  
Specific target organ toxicity (repeated exposure), Category 2 (STOT RE 2, H373).  
Aspiration hazard, Category 1 (Asp. Tox. 1, H304).  
Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

### 2.2. Label elements

#### In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



Signal Word :

DANGER

Product identifiers :

EC 215-535-7 XYLENE  
EC 200-662-2 ACETONE  
EC 919-857-5 HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS  
CAS 160901-19-9 ALCOHOLS, C12-13, BRANCHED AND LINEAR, ETHOXYLATED

Hazard statements :

H225 Highly flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H332 Harmful if inhaled.

H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure .
H412	Harmful to aquatic life with long lasting effects.
Precautionary statements - Prevention :	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary statements - Response :	
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P302 + P352	IF ON SKIN: Wash with plenty of water
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor/.../if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P331	Do NOT induce vomiting.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
Precautionary statements - Storage :	
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
Precautionary statements - Disposal :	
P501	Dispose of contents / container in accordance with local / regional / national / international regulations



### 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq 0.1\%$  published by the European CHemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>  
The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

## SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures



#### Composition :

Identification	(EC) 1272/2008	Note	%
CAS: 1330-20-7 EC: 215-535-7  XYLENE	GHS07, GHS08, GHS02 Dgr Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335 STOT RE 2, H373	[1]	25 $\leq$ x % < 50
CAS: 67-64-1 EC: 200-662-2 REACH: 01-2119471330-49  ACETONE	GHS07, GHS02 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH:066	[1]	10 $\leq$ x % < 25
CAS: 64742-48-9 EC: 919-857-5  HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS	GHS07, GHS08, GHS02 Dgr Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 EUH:066		10 $\leq$ x % < 25
CAS: 67-63-0	GHS07, GHS02	[1]	10 $\leq$ x % < 25

EC: 200-661-7 PROPAN-2-OL	Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336		
EC: 920-134-1 REACH: 01-2119480153-44  HYDROCARBONS, C9-C11, ISOALKANES, CYCLICS, <2% AROMATICS	GHS09, GHS07, GHS08, GHS02 Dgr Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411 EUH:066		10 <= x % < 25
CAS: - EC: -  POLYETHERAMINE	GHS07, GHS09 Wng Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 2, H411		2.5 <= x % < 10
CAS: 160901-19-9  ALCOHOLS, C12-13, BRANCHED AND LINEAR, ETHOXYLATED	GHS07, GHS05 Dgr Acute Tox. 4, H302 Eye Dam. 1, H318 Aquatic Chronic 3, H412		2.5 <= x % < 10

(Full text of H-phrases: see section 16)



#### Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

## SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

### 4.1. Description of first aid measures

#### In the event of exposure by inhalation :

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

Do not proceed with mouth-to-mouth or mouth-to-nose resuscitation. Use the appropriate equipment.

Remove the victim to fresh air. If the symptoms persist, call a physician.

#### In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

Wash immediately and abundantly with water, including under the eyelids.

#### In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

Immediately remove all soiled clothing.

Wash immediately and abundantly with soap and water.

#### In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Seek medical attention immediately, showing the label.

If swallowed accidentally, do not allow to drink, do not induce vomiting and transfer to hospital immediately by ambulance. Show the label to the doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

No data available.

### 4.3. Indication of any immediate medical attention and special treatment needed

No data available.

## SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

### 5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

### Suitable methods of extinction

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Dry agent, foam, carbon dioxide.

### Unsuitable methods of extinction

High volume water jet

### 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)

- carbon dioxide (CO<sub>2</sub>)

### 5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

## SECTION 6 : ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

Spilled product may make surfaces slippery.

### For non first aid worker

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

### For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

### 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Use drums to dispose of collected waste in compliance with current regulations (see section 13).

### 6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

### 6.4. Reference to other sections

No data available.

## SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

### 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Remove contaminated clothing and protective equipment before entering eating areas.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

Do not swallow

Do not get in eyes, on skin, or on clothing.

### Fire prevention :

Handle in well-ventilated areas.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Never inhale this mixture.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged: always ground when decanting. Wear antistatic shoes and clothing and make floors of

non-conductive

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Take precautionary measures against static discharges by bonding and grounding equipment.

No smoking.

#### Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Avoid eye contact with this mixture at all times.

Avoid exposure - obtain special instructions before use.

Ensure good ventilation at the workplace

#### Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

Never open the packages under pressure.

Do not breathe fumes, vapour, spray.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store between 5°C and 40°C in a dry, well ventilated place.

Only use hydrocarbon-resistant containers, joints and pipes.

#### Storage

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from food and drink, including those for animals.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Avoid accumulation of electrostatic charges.

#### Packaging

Always keep in packaging made of an identical material to the original.

#### 7.3. Specific end use(s)

No data available.

## SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Occupational exposure limits :

- European Union (2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

CAS	VME-mg/m <sup>3</sup> :	VME-ppm :	VLE-mg/m <sup>3</sup> :	VLE-ppm :	Notes :
1330-20-7	221	50	442	100	Peau
67-64-1	1210	500	-	-	-

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
1330-20-7	100 ppm	150 ppm		A4; BEI	
67-64-1	500 ppm	750 ppm		A4; BEI	
67-63-0	200 ppm	400 ppm		A4; BEI	

- Germany - AGW (BAuA - TRGS 900, 08/08/2019) :

CAS	VME :	VME :	Excess	Notes
1330-20-7		100 ppm 440 mg/m <sup>3</sup>		2(II)
67-64-1		500 ppm 1200 mg/m <sup>3</sup>		2(I)
67-63-0		200 ppm 500 mg/m <sup>3</sup>		2(II)

- France (INRS - ED984 / 2019-1487) :

CAS	VME-ppm :	VME-mg/m <sup>3</sup> :	VLE-ppm :	VLE-mg/m <sup>3</sup> :	Notes :	TMP No :
1330-20-7	50	221	100	442	*	4 Bis. 84. *
67-64-1	500	1210	1000	2420	-	84
67-63-0	-	-	400	980	-	84

- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
1330-20-7	50 ppm 220 mg/m <sup>3</sup>	100 ppm 441 mg/m <sup>3</sup>		Sk. BMGV	
67-64-1	500 ppm 1210 mg/m <sup>3</sup>	1500 ppm 3620 mg/m <sup>3</sup>			
67-63-0	400 ppm 999 mg/m <sup>3</sup>	500 ppm 1250 mg/m <sup>3</sup>			

## 8.2. Exposure controls

### Appropriate engineering controls

Ensure adequate ventilation, if possible with extractor fans at work posts and appropriate general extraction.  
Personnel shall wear regularly laundered overalls.

### Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

#### - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

#### - Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

Glove thickness:	0.38 mm
Break-through time:	> 480 mn

Recommended properties :

- Impervious gloves in accordance with standard EN ISO 374-2

#### - Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

#### - Respiratory protection

Avoid breathing vapours.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

Breathing apparatus only when aerosol or spray are formed.

## SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

**9.1. Information on basic physical and chemical properties****General information :**

Physical state :	Fluid liquid.
Color:	red

**Important health, safety and environmental information**

pH :	Not relevant.
Boiling point/boiling range :	> 35°C
Flash Point :	-9.00 °C.
Vapour pressure (50°C) :	Not relevant.
Density :	< 1
Water solubility :	Insoluble.
Viscosity:	v < 7 mm <sup>2</sup> /s (40°C)

**9.2. Other information**

No data available.

**SECTION 10 : STABILITY AND REACTIVITY****10.1. Reactivity**

No data available.

**10.2. Chemical stability**

This mixture is stable under the recommended handling and storage conditions in section 7.

**10.3. Possibility of hazardous reactions**

No data available.

**10.4. Conditions to avoid**

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- accumulation of electrostatic charges.
- heating
- heat
- flames and hot surfaces

Keep away from heat and from sources of ignition

Take precautionary measures against static discharges.

**10.5. Incompatible materials**

Strong oxidants

Acids

**10.6. Hazardous decomposition products**

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

**SECTION 11 : TOXICOLOGICAL INFORMATION****11.1. Information on toxicological effects**

Harmful by inhalation.

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

May have irreversible effects on the eyes, such as tissue damage in the eye, or serious physical decay of sight, which is not fully reversible by the end of observation at 21 days.

Serious eye damage is typified by the destruction of cornea, persistent corneal opacity and iritis.

Respiratory tract irritation may occur, together with symptoms such as coughing, choking and breathing difficulties.

Narcotic effects may occur, such as drowsiness, narcosis, decreased alertness, loss of reflexes, lack of coordination or dizziness.

Effects may also occur in the form of violent headaches or nausea, judgement disorder, giddiness, irritability, fatigue or memory disturbance.

May cause severe damage to organs in the event of repeated or prolonged exposure.

Aspiration toxicity includes severe acute effects such as chemical pneumonia, varying degrees of pulmonary injury or death following aspiration.

**11.1.1. Substances****Acute toxicity :**

XYLENE (CAS: 1330-20-7)

Dermal route :

LD50 = 1100 mg/kg

Inhalation route (n/a) :	LC50 = 11 mg/l Duration of exposure : 4 h
ALCOHOLS, C12-13, BRANCHED AND LINEAR, ETHOXYLATED (CAS: 160901-19-9) Oral route :	LD50 = 500 ml/kg
POLYETHERAMINE (CAS: -) Oral route :	LD50 > 5000 mg/kg Species : Rat
Dermal route :	LD50 > 2000 mg/kg Species : Rabbit
HYDROCARBONS, C9-C11, ISOALKANES, CYCLICS, <2% AROMATICS Oral route :	LD50 > 5000 mg/kg Species : Rat OCDE Ligne directrice 401 (Toxicité aiguë par voie orale)
Dermal route :	LD50 > 5000 mg/kg Species : Rat
Inhalation route (n/a) :	LC50 > 5 mg/l Species : Rat
PROPAN-2-OL (CAS: 67-63-0) Oral route :	LD50 = 5840 mg/kg Species : Rat OCDE Ligne directrice 423 (Toxicité aiguë par voie orale - Méthode de la classe de toxicité aiguë)
Dermal route :	LD50 = 12857 mg/kg Species : Rabbit OCDE Ligne directrice 402 (Toxicité aiguë par voie cutanée)
Inhalation route (n/a) :	LC50 10000 Species : Rat OCDE Ligne directrice 403 (Toxicité aiguë par inhalation)
HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS (CAS: 64742-48-9) Oral route :	LD50 > 8000 mg/kg Species : Rat
Dermal route :	LD50 > 4000 mg/kg Species : Rat
Inhalation route (n/a) :	LC50 18.5 Species : Rat
ACETONE (CAS: 67-64-1) Oral route :	LD50 = 5800 mg/kg Species : Rat
Dermal route :	LD50 = 20000 mg/kg Species : Rabbit
Inhalation route (n/a) :	LC50 = 76 mg/l Species : Rat Duration of exposure : 4 h

**11.1.2. Mixture****Acute toxicity :**

Inhalation route (Dusts/mist) : Harmful by inhalation.



Duration of exposure : 4 h  
LC50 = 4.286 mg/l

**Skin corrosion/skin irritation :**

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non allergic contact dermatitis and absorption through the skin.

**Aspiration hazard :**

May be fatal if swallowed and enters airways.

Aspiration toxicity includes severe acute effects such as chemical pneumonia, varying degrees of pulmonary injury or death following aspiration.

"Inhalation of vapours may cause irritation of the respiratory system in very susceptible persons."

May cause lung damage if swallowed

 **Monograph(s) from the IARC (International Agency for Research on Cancer) :**

CAS 67-63-0 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

CAS 1330-20-7 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

**SECTION 12 : ECOLOGICAL INFORMATION**

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

**12.1. Toxicity** **12.1.1. Substances**

POLYETHERAMINE (CAS: -)

Fish toxicity : 1 < LC50 <= 10 mg/l  
Duration of exposure : 96 h

Algae toxicity : 10 < ECr50 <= 100 mg/l  
Duration of exposure : 72 h

HYDROCARBONS, C9-C11, ISOALKANES, CYCLICS, <2% AROMATICS

Fish toxicity : LC50 = 3.6 mg/l  
Species : Oncorhynchus mykiss  
Duration of exposure : 96 h  
OCDE Ligne directrice 203 (Poisson, essai de toxicité aiguë)

Crustacean toxicity : EC50 = 22 mg/l  
Species : Daphnia magna  
Duration of exposure : 48 h  
OCDE Ligne directrice 202 (Daphnia sp., essai d'immobilisation immédiate)

Algae toxicity : ECr50 > 1000 mg/l  
Species : Pseudokirchnerella subcapitata  
Duration of exposure : 72 h  
OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance)

PROPAN-2-OL (CAS: 67-63-0)

Fish toxicity : LC50 > 100 mg/l  
Species : Leuciscus idus  
Duration of exposure : 96 h

Crustacean toxicity : EC50 > 100 mg/l  
Species : Daphnia magna  
Duration of exposure : 48 h

Algae toxicity : ECr50 > 100 mg/l  
Species : Scenedesmus subspicatus  
Duration of exposure : 72 h

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS (CAS: 64742-48-9)

Fish toxicity : LC50 > 1000 mg/l  
Species : Oncorhynchus mykiss  
Duration of exposure : 96 h

Crustacean toxicity : EC50 > 1000 mg/l

Species : Daphnia magna  
Duration of exposure : 48 h

Algae toxicity :  
ECr50 > 1000 mg/l  
Species : Pseudokirchnerella subcapitata  
Duration of exposure : 72 h

ACETONE (CAS: 67-64-1)  
Fish toxicity :  
LC50 = 5540 mg/l  
Species : Oncorhynchus mykiss  
Duration of exposure : 96 h

Crustacean toxicity :  
EC50 = 6100 mg/l  
Species : Daphnia magna  
Duration of exposure : 48 h

### 12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

## 12.2. Persistence and degradability

### 12.2.1. Substances

POLYETHERAMINE (CAS: -)  
Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

HYDROCARBONS, C9-C11, ISOALKANES, CYCLICS, <2% AROMATICS  
Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

PROPAN-2-OL (CAS: 67-63-0)  
Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS (CAS: 64742-48-9)  
Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

ACETONE (CAS: 67-64-1)  
Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

### 12.3. Bioaccumulative potential

No data available.

### 12.4. Mobility in soil

Not very mobile in soil.  
The product is insoluble in water and will spread on the surface

### 12.5. Results of PBT and vPvB assessment

No data available.

### 12.6. Other adverse effects

Do not dispose of the product in the natural environment, effluents or surface waters.

### German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :

WGK 2 : Hazardous for water.

## SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

### 13.1. Waste treatment methods

Do not pour into drains or waterways.

#### Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

Empty container completely. Keep label(s) on container.  
Give to a certified disposal contractor.

**SECTION 14 : TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2019 - IMDG 2018 - ICAO/IATA 2020).

**14.1. UN number**

1993

**14.2. UN proper shipping name**

UN1993=FLAMMABLE LIQUID, N.O.S.  
(xylene, acetone)

**14.3. Transport hazard class(es)**

- Classification :



3

**14.4. Packing group**

II

**14.5. Environmental hazards**

-

**14.6. Special precautions for user**

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	3	F1	II	3	33	1 L	274 601 640C	E2	2	D/E
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation	
	3	-	II	1 L	F-E, S-E	274	E2	Category B	-	
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	3	-	II	353	5 L	364	60 L	A3	E2	
	3	-	II	Y341	1 L	-	-	A3	E2	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

No data available.

**SECTION 15 : REGULATORY INFORMATION****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****- Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2020/217 (ATP 14)

**- Container information:**

No data available.

**- Particular provisions :**


No data available.

**- German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :**

WGK 2 : Hazardous for water.

**- Standardised American system for the identification of hazards presented by the product in view of emergency procedures (NFPA 704) :**

NFPA 704, Labelling: Health=3 Inflammability=3 Instability/Reactivity=1 Specific Risk=none



## 15.2. Chemical safety assessment

No data available.

## SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.



### Wording of the phrases mentioned in section 3 :

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure .
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

### Abbreviations :

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS05 : Corrosion

GHS07 : Exclamation mark

GHS08 : Health hazard

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.