



SNOWPOWER 2T

2 stroke engine lubricant for Snowmobile

Technosynthese® - Ester

TYPE OF USE

Specially formulated for snowmobile with 2 stroke engines working under the most extreme weather conditions: polar cold.

All snowmobile 2 stroke engines with injector systems or lubricated by premix.

All type of use including racing.

PERFORMANCE

STANDARDS API TC
 ISO-L-EGD
SPECIFICATIONS JASO FD under N°033MOT068

Synthetic lubricant Technosynthese® - Ester based with low pour point (-45°C / -49°F) formulated with a low content of solvent for easy start up at very low temperature.

Low ash formulation lubricant, Ester based with an effective detergent & dispersant power for a perfect piston, chamber and power valves cleanliness.

Mixes instantaneously with gasoline and remains stable.

Reduces friction and wear to increase engine life.

Anti-smoke.

RECOMMENDATIONS

Mixing ratio: from 2% to 4% (from 50:1 to 25:1) according to manufacturers' requirements and adjust according to your own use.

PROPERTIES

Color	Visual	Blue
Density at 20°C (68°F)	ASTM D1298	0.856
Viscosity at 40°C (104°F)	ASTM D445	43.1 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	7.04 mm ² /s
Viscosity index	ASTM D2270	123
Flash point	ASTM D92	146°C / 295°F
Pour point	ASTM D97	-45°C / -49°F
TBN	ASTM D2896	2.0 mg KOH/g