

MP 20 EPDM



Multi-Purpose Hose

Application:

Highly flexible multi-purpose hose, with very good ageing, weather and abrasion resistance.

Suitable for conveying air and water, as well as many chemical products in industry and agriculture (see resistance list).

Feature:

High EPDM quality ensures excellent ozone and weather resistance.

Kink resistant due to textile reinforcement.

Electrically conductive tube construction prevents the build-up of static electricity. $R < 10^6 \Omega$ (according to EN ISO 8031:1997).

Notice:

If in any doubt regarding use, please contact Semperit.

ATTENTION: Please refer to the Semperit resistance list or, in case of doubt, contact Semperit.

ATTENTION: The temperature of the medium must be lower than its boiling point.

Temperature range:

-40°C / + 95°C, briefly up to 110°C.

Safety factor:

4 : 1

Tube:

EPDM, black, smooth, electrically conductive.

Reinforcement:

Textile spiral construction.

Cover:

EPDM, black, 3 blue longitudinal stripes, smooth, electrically conductive, ozone and weather resistant.

Marking:

continuous coloured marking, white:

"SEMPERIT S MP 20-EPDM MULTI PURPOSE PN 20 BAR DN"



Article number	Internal-Ø in		Wall width	External-Ø		Work. pressure (max.) bar	Number of inserts	Bending radius (min.) in mm	Weight approx. kg/m	Coil length (max.) m
	mm	inch	in mm	in mm						
68024 0635	6,0	1/4	3,5	13,0	20	2	40	0,15	100	
68024 0835	8,0	5/16	3,5	15,0	20	2	50	0,18	100	
68024 1035	10,0	3/8	3,5	17,0	20	2	60	0,21	100	
68024 1340	13,0	1/2	4,0	21,0	20	2	80	0,30	100	
68024 1640	16,0	5/8	4,0	24,0	20	2	100	0,35	100	
68024 1945	19,0	3/4	4,5	28,0	20	2	115	0,47	50	
68024 2550	25,0	1	5,0	35,0	20	2	150	0,67	50	
68024 3260	32,0	1 1/4	6,0	44,0	20	4	200	1,05	50	
68024 3860	38,0	1 1/2	6,0	50,0	20	4	250	1,20	50	

Please note: Before using our products with new or untested media, or for applications that are not clearly indicated in the product information, written advice must be obtained from a specialist dealer or a Semperit application engineer. For safety reasons, all products must be inspected regularly for operational safety and replaced in the event of any damage (especially of the cover) or unusual signs of wear and tear. All products must be stored, handled and maintained in accordance with all our respective instructions and DIN 7716:1982. The information in our catalogue as well as each individual datasheet is subject to change at any time without notice since we are constantly developing and improving our products and due to constant technical developments after the latest release date of the catalogue and/or individual datasheets. In order to always have the latest product and safety information make sure you visit our website (www.semperflex.com) regularly or contact one of our specialist dealers or a Semperit application engineer. All contracts with Semperflex are exclusively subject to our general terms and conditions (available at www.semperitgroup.com). Additional important general information about the range, choice and safe use of our products can be found at our website (www.semperflex.com) and must be followed without exception.

Important notice: Our catalogue and any individual datasheet have been prepared with great care in order to provide you with all the information you need. The information contained therein is based on the latest state-of-the-art industrial technology and many years of experience and testing; whenever indicated for a certain product, we also confirm conformity with the resistance requirements of the media listed in ISO TR 7620: 2005(E). However, the individual conditions of storage, maintenance and use decisively affect the safe and durable use of each product. The quality and safety of our products as indicated in the catalogue or individual datasheets are therefore strictly subject to the continuous observance of all specifications and restrictions in our written product information and applicable laws and standards, the specifications regarding resistance to chemicals and our cleaning procedures. We reject any liability for safety issues or other consequences due to improper product choice, maintenance or handling (e.g. squashing, rupturing, stretching or filling with non-approved media). Our products must not be used in airplanes or other aerial vehicles under any circumstance. Unless specified otherwise, all hoses are manufactured according to EN ISO 1307:2008.