



Typical Inspection Data:

Density @ 20°C	0.853 g/cm ³
Viscosity @ 100°C	9.6 cSt
Viscosity @ 40°C	53 cSt
Viscosity Index	168
Viscosity CCS @ -35°C	5900 cP
T.B.N.	9.7 mg KOH/g
Sulphated Ash Mass	1.2%
Zinc	0.14%
Calcium	0.28%
Phosphorus	0.12%
Colour	Amber
Flash Point	>200°C
Pour Point	-42°C

Pro-VLL 0W-30

Fully Synthetic

Official Approvals:

Approved under VW standard 503 00 and VW standard 506 01

Recommended by Comma for applications requiring:

VW 506 00

Product Features:

- Fully synthetic, high performance fuel-economy promoting engine oil, developed specifically for diesel PD Volkswagen engines running on LongLife Service regime.
- To ensure correct oil selection use Comma's latest application guide instore or online at www.CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 16-11-2018