

### **Technical** Data Sheet



### Typical Inspection Data: Density @ 20°C 0.847 g/cm<sup>3</sup> Viscosity @ 100°C 17.6 cSt Viscosity @ 40°C 106 cSt Viscosity Index 183 Viscosity CCS @ -30°C 5500 cP T.B.N. 8.4 mg KOH/g Sulphated Ash Mass 1.0% Zinc 0.10% Calcium 0.25% **Phosphorus** 0.09% Colour Brown Flash Point 230°C **Pour Point** -39°C

## **Motorsport 5W-50**

Fully Synthetic

# Recommended by Comma for applications requiring:

Suitable for replacing SAE 5W-40, 10W-40 & 15W-40 oils in Motorsport applications.

### **Product Features:**

- Fully synthetic, high performance 5W-50 oil, for motorsport and track day use.
- Track tested to give high performance under extreme race conditions.
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com

### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### **Shelf Life:**

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

**UPDATED: 09-07-2019**