

# Technical Data Sheet



Typical Inspection Data:	
Density @ 20°C	0.847 g/cm <sup>3</sup>
Viscosity @ 100°C	12.2 cSt
Viscosity @ 40°C	73 cSt
Viscosity Index	165
Viscosity CCS @ -30°C	5900 cP
T.B.N.	8.0 mg KOH/g
Sulphated Ash Mass	0.49%
Zinc	0.07%
Phosphorus	0.05%
Colour	Brown
Flash Point	230°C
Pour Point	-39°C

### Ecoren 5W-30

### Fully Synthetic

### **Official Approvals:**

Approved by Renault to meet RN0720

## Recommended by Comma for applications requiring:

MB 226.51 ACEA C4

#### **Product Features:**

- Fully synthetic, high performance 5W-30 low SAPS oil for modern petrol and diesel vehicles including those fitted with exhaust after-treatment units that require an ACEA C4 grade.
- Do not mix this oil with other Types of oil, as therequirement for exhaust after-treatment protection will no longer be guaranteed.
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com

### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight diget code printed on the bottle. YYYY.MM.DD.

#### UPDATED: 20/11/2019