



Typical Inspection Data:

Density @ 20°C	0.850 g/cm ³
Viscosity @ 100°C	14.2 cSt
Viscosity @ 40°C	87 cSt
Viscosity Index	169
Viscosity CCS @ -30°C	6000 cP
T.B.N.	8.0 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.10%
Calcium	0.18%
Phosphorus	0.08%
Colour	Brown
Flash Point	230°C
Pour Point	-39°C

PD Plus 5W-40

Fully Synthetic

Official Approvals:

Approved under VW standard 505 00 and VW standard 505 01

Recommended by Comma for applications requiring:

FORD WSS M2C917-A; VW 502 00; MB 229.31, MB 226.5; RN0700, RN 0710; dexos 2; ACEA C3; API SN CF

Product Features:

- For VW PD/unit injector engines operating on fixed service intervals.
- Fully synthetic, high performance, 5W-40 oil, for vehicles fitted with the VW 'Pumpe Düse' PD or unit injector engine. Also protects exhaust after-treatment units.
- Do not mix this oil with other types of oil as the exhaust after-treatment protection will no longer be guaranteed.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 25-01-2021