



### Typical Inspection Data:

Density @ 20°C	1.060 g/cm <sup>3</sup>
Viscosity @ -40°C	700 cSt
Viscosity @ 100°C	2.1 cSt
Colour	Colourless to amber
Equilibrium Reflux Boiling Point	265°C
Wet Equilibrium Reflux Boiling Point	170°C
pH (50% EtOH)	8.1

## DOT 4 ESP

### Synthetic Brake Fluid

**Recommended by Comma for applications requiring:**

FMVSS 116 DOT 4, ISO 4925 (Classes 3, 4 & 6), SAE J1703, SAE J1704

### Product Features:

- Specially formulated for use in cars with ABS.
- For improved braking and faster anti-skid reaction at low temperatures.
- Can be mixed safely with DOT 4 fluids.

### Directions for use:

- **IMPORTANT** - Follow vehicle manufacturer's recommendations.
- Keep Brake Fluid clean and dry.
- Store in original container only.
- Keep container clean and tightly closed to prevent water absorption.
- Caution: Do not refill container and do not use for other liquids.
- Take care not to spill on paintwork. If spilt wash off with plenty of water. Do not rub.
- All brake fluids absorb moisture and therefore they must be checked or changed regularly.

### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### Shelf Life:

- 3 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 03-03-2021