



Classic 20W-50

Mineral

Official Approvals:

SAE 20W-50
API SE CC

Product Features:

- Specially blended for Classic Cars from the 60's, 70's and 80's where an oil of this quality and viscosity is recommended by the manufacturer.
- Ideal for use in classic-stroke petrol cars, non turbo charged.
- Protects and preserves classic engines.
- Ensures economical consumption.

Typical Inspection Data:

Density @ 20°C	0.870 g/cm ³
Viscosity @ 100°C	17.2 cSt
Viscosity @ 40°C	145 cSt
Viscosity Index	120
Viscosity CCS @ -15°C	8000 cP
Sulphated Ash Mass	1.1%
Zinc	0.08%
Calcium	0.22%
Phosphorus	0.07%
Colour	Green
Pour Point	-27°C

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 29-06-2021

Moove Lubricants Ltd. Dering Way, Gravesend, Kent DA12 2QX, England.

Tel: +44 (0)1474 564 311, Fax: +44(0)1474 333 000 Email: sales@commaoil.com www.CommaOil.com