



Typical Inspection Data:

Density @ 20°C	0.845 g/cm ³
Viscosity @ 100°C	10.0 cSt
Viscosity @ 40°C	56 cSt
Viscosity Index	167
Viscosity CCS @ -30°C	4000 cP
T.B.N.	8.0 mg KOH/g
Sulphated Ash Mass	0.49%
Zinc	0.07%
Phosphorus	0.05%
Colour	Brown
Flash Point	230°C
Pour Point	-42°C

Ecolife 5W-30

Fully Synthetic

Official Approvals:

Verified by Jaguar Land Rover to meet the requirements of STJLR.03.5005

Renewal approval application submitted to the OEM. Certification process delayed by OEM due to Covid-19. Expected to be completed by Sept-21.

Recommended by Comma for applications requiring:

FORD WSSM2C934-B, ACEA C1

Product Features:

- Fully synthetic, high performance 5W-30 low SAPS oil for modern petrol and diesel vehicles including those fitted with exhaust after-treatment units that require an ACEA C1 grade.
- Do not mix this oil with other types of oil, as the requirement for exhaust after-treatment protection will no longer be guaranteed.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 21-06-2021

Moove Lubricants Ltd. Dering Way, Gravesend, Kent DA12 2QX, England.

Tel: +44 (0)1474 564 311, Fax: +44(0)1474 333 000 Email: sales@commaoil.com www.CommaOil.com