



## **SUPERCOLDMASTER COOLANT**

### **APPLICATION**

- A Mono Ethylene Glycol (MEG) based engine coolant.
- Suitable for use in all types of vehicle requiring an MEG coolant.

### **PROPERTIES**

- Protects for 2 years.
- -36 Winter protection.
- +45 Summer protection.
- Helps prevent winter freezing and summer boil over. Also improves heat transfer.
- NAP (Nitrite, Phosphate and Amine) free.
- Suitable for Ferrous and Aluminium engines.
- Meets BS6580 – 1992, AFNOR NFR 15-601.

### **TYPICAL INSPECTION DATA**

Appearance	Clear blue / green liquid
Specific Gravity @ 20°C	1.073

### **DIRECTIONS FOR USE**

- Ready to use but for maximum protection first drain and flush cooling system.
- For full protection do not mix with other fluids.
- Minor spills should be soaked up with oil absorbent granules, sand or dirt. The spillage site should then be washed with soapy water and dried.

### **HANDLING**

- Wash off any spillage on paintwork immediately.
- Keep away from foodstuffs and oxidising agents.
- Store in airtight container.
- Avoid galvanised containers for storage or dispensing as they will corrode and contaminate the product.

### **SHELF LIFE**

- 3 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.