



## Product Name:

TransFlow GX 15W-40

## Comma recommends this product for applications requiring:

ACEA E9; API CJ-4 SM

MB 228.31; MAN 3275; Volvo VDS-4; RVI RLD-3; Cat ECF-3; Cummins CES 20081; MACK EO-O Premium Plus

## Application:

- Mineral, 15W-40 oil, suitable for use in diesel engines meeting Euro V emissions requirements.
- Ideal for use with low sulphur fuel.
- To ensure correct oil selection check Comma's latest Application guide in store or online at [www.CommaOil.com](http://www.CommaOil.com).

## Typical Inspection Data:

Specific Gravity at 20° C	0.869
Viscosity at 100°C	14.8 cSt
Viscosity at 40°C	108 cSt
Viscosity Index	145
Viscosity CCS at -20°C	5500 cP
T.B.N.	7.7 mg KOH/g
Sulphated Ash Mass	1.0%
Zinc	0.13%
Calcium	0.11%
Phosphorous	0.12%
Colour	Brown
Flash Point	200°C
Pour Point	-30°C

## Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

## Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the day of the year, the last two figures the year.