



X-Flow Type G 5W-40

Fully Synthetic

Recommended by Comma for applications requiring:

MB 229.1; VW 502 00, VW 505 00; RN0700, RN0710
ACEA A3/B4
API SL CF

Product Features:

- Fully synthetic 5W-40 oil suitable for petrol and diesel vehicles including those with fuel injected, multivalved and turbo charged engines.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Typical Inspection Data:

Density @ 20°C	0.853 g/cm ³
Viscosity @ 100°C	13.8 cSt
Viscosity @ 40°C	81 cSt
Viscosity Index	170
Viscosity CCS @ -30°C	5900 cP
T.B.N.	10.6 mg KOH/g
Sulphated Ash Mass	1.1%
Zinc	0.12%
Calcium	0.30%
Phosphorus	0.11%
Colour	Brown
Flash Point	230°C
Pour Point	-39°C

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 03.05.2019