



XSTREAM G30 ANTIFREEZE & COOLANT READY MIXED

APPLICATION

- A high quality OEM approved MEG based engine coolant.
- Ready mixed with treated water to prevent scaling of waterways.
- For suitability guidance see Comma Application Guide or Web Page.

PROPERTIES

- High performance vehicle manufacturer approved antifreeze.
- Protects for 5 years.
- Helps prevent winter freezing and summer boil over.
- BASF Glysantin formulation (G30, VW G12, G12+).
- NAP (Nitrite, Phosphate and Amine), Silicate and Borax free.
- Organic Acid Technology (OAT).
- Designed to protect modern aluminium engines.
- Suitable for a wide range of modern heavy duty diesel engines where a nitrite free coolant is required e.g. some Scania, DAF and Volvo models.
- Meets the requirements of BS6580 – 1992
Ford WSS-M97B44-D
VAG (Vauxhall, Audi, Seat, Skoda) TL 774 D/F
MTU MTL 5048
MAN 324-SNF
Mercedes-Benz DBL 7700.30 / 325.3

TYPICAL INSPECTION DATA

Appearance	Clear red liquid
Specific Gravity @ 20 °C	1.074
Protects to	-34 °C

DIRECTIONS FOR USE

- Miscible with other fluids but for maximum protection systems should be drained, flushed and refilled.

HANDLING

- Minor spills should be soaked up with oil absorbent granules, sand or dirt. The spillage site should then be washed with soapy water and dried.
- Wash off any spillage on paintwork immediately.
- Avoid galvanised containers for storage or dispensing as they will corrode and contaminate the product.

SHELF LIFE

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.