



Xstream® G05® Antifreeze & Coolant - Concentrate

APPLICATION

- Heavy Duty ethylene glycol based antifreeze for use in vans & trucks.
- Protects against corrosion, overheating and freezing.
- Typical service life of up to 6,000 hours.
- Safeguarded with bittering agent to help prevent accidental ingestion.
- To ensure correct antifreeze & coolant selection check Comma's latest application guide in store or online at www.CommaOil.com.

Glysantin® G05® by BASF is approved by:

Chrysler (MS 9769), John Deere (JDM H 24), JCB (STD00088), MTU (MTL 5048), Mercedes Benz (325.0), MAN B&W (List 3.3.7), Cummins (CES 14603).

This Engine Coolant Concentrate conforms to the requirements of BS 6580:2010

TYPICAL INSPECTION DATA

Appearance	Clear yellow liquid
Specific Gravity @ 20 °C	1.130
Boiling Point	Min 170 °C

PROTECTION LEVELS / DILUTION CHART

Xstream® G05® (%)	Approx. Protection (°C)
33	-18
50	-36
60	-52

DIRECTIONS FOR USE

1. Dilute with de-ionised water in accordance with the vehicle manufacturer's instructions.
2. Pour into vehicle cooling system.
3. Do not mix different types of Antifreezes. If in doubt about product suitability, refer to vehicle handbook.
4. Remove spills from paintwork immediately.

HANDLING

- Minor spills should be soaked up with oil absorbent granules, sand or dirt. The spillage site should then be washed with soapy water and dried.
- Wash off any spillage on paintwork immediately.
- Avoid galvanised containers for storage or dispensing as they will corrode and contaminate the product.

SHELF LIFE

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the day of the year, the last two figures the year.