

# **Technical** Data Sheet



# Typical Inspection Data: Density @ 20 °C 0.865 g/cm³ Viscosity @ 100 °C 16.0 cSt Viscosity @ 40 °C 100 cSt Calcium 0.29% Phosphorus 0.05% Colour Brown Pour Point -39 °C

### **Performance Profile:**

Recommended by Comma for certain Ford, Vauxhall, Mazda, Volvo & VAG Group applications and generally where a 75W-90, API GL-4 oil is specified. Suitable for use where the following specifications are called for:

BMW MTF LT-4, Ford WSD-M2C200-C, Ford WSD-M2C200-B, GM 1940768, GM 1940182, GM 1940764, Volvo 97309, Volkswagen G 50, API GL-4 (75W-85), API GL-4 synthetic (75W-85 & 75W-90)

# **MVMTF Plus 75W-90**

# Fully Synthetic

### **Product Features:**

- Fully synthetic manual transmission fluid with excellent bearing and gear protection and proven synchroniser performance.
- Good low temperature performance.
- Excellent cleanliness.
- Robust corrosion protection.
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com.

## Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Modified 11.01.2021

**Moove Lubricants Ltd.** Dering Way, Gravesend, Kent DA12 2QX, England.
Tel: +44 (0)1474 564 311, Fax: +44(0)1474 333 000 Email: sales@commaoil.com www.CommaOil.com