



TransFlow AD 10W-40 Semi Synthetic

Recommended by Comma for applications requiring:

ACEA A3/B4 E7; API CI-4; MAN 3275;
Cummins CES 20077/78; MTU Type 2; MACK EO-M+

Official Approvals:

TransFlow AD 10W-40 is officially approved by:
MB-Approval 228.3; Volvo VDS-3; Renault RLD-2;
MACK EO-N

Product Features:

- Semi-synthetic, 10W-40 oil, suitable for high performance diesel engines including turbo charged and naturally aspirated.
- Ideal for mixed fleet-trucks.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:

Density @ 20°C	0.865 g/cm ³
Viscosity @ 100°C	14.4 cSt
Viscosity @ 40°C	95 cSt
Viscosity Index	150
Viscosity CCS @ -25°C	5400 cP
T.B.N.	10.1 mg KOH/g
Sulphated Ash Mass	1.4%
Zinc	0.11%
Calcium	0.38%
Phosphorus	0.12%
Colour	Dark Brown
Flash Point	230°C
Pour Point	-33°C

UPDATED: 01.07.2021