



## **X-FLOW TYPE F 5w30 SEMI-SYNTHETIC MOTOR OIL**

### **APPLICATION**

- Suitable for high performance petrol engines including fuel injected, multivalved and Ford Zetec engines.
- Enhanced protection in all conditions – cold to heat.
- Provides supreme performance with fuel efficiency and helps reduce emissions.

### **SPECIFICATIONS**

- SAE 5w30
- API SL CF
- ACEA A1 B1

### **TYPICAL INSPECTION DATA**

Specific gravity at 20°C	0.852
Viscosity @ 100°C	10.4 cSt
Viscosity @ 40°C	58 cSt
Viscosity Index	165
Viscosity CCS @ -30°C	5600 cP
T.B.N.	6.5 mg KOH/g
Sulphated Ash Mass	1.1%
Zinc	0.11%
Calcium	0.24%
Phosphorus	0.11%
Colour	Brown

### **HANDLING**

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### **SHELF LIFE**

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.