



X-FLOW TYPE S 10w40 SEMI-SYNTHETIC MOTOR OIL

APPLICATION

- Suitable for high performance petrol and diesel engines including fuel injected, turbo charged and naturally aspirated.
- Enhanced protection in all conditions – cold to heat.

SPECIFICATIONS

- SAE 10w40
- API SL CF
- ACEA A3 B3
- VW 501.01 / 505.00

TYPICAL INSPECTION DATA

Specific gravity at 20°C	0.870
Viscosity @ 100°C	13.8 cSt
Viscosity @ 40°C	88 cSt
Viscosity Index	150
Viscosity CCS @ -25°C	6500 cP
T.B.N.	6.8 mg KOH/g
Sulphated Ash Mass	1.0%
Zinc	0.15%
Calcium	0.18%
Phosphorus	0.14%
Colour	Brown

HANDLING

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

SHELF LIFE

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.