

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.11.2021

V- 2.0

Revision: 21.05.2018

* **SECTION 1: Identification of the substance/mixture and of the company/
undertaking**

1.1 Product identifier

Trade name: **0RS001, 0RS005, 0RS006, 0RS007, 0RS008, 0RS009, 0RS018, 0RS020,
0RS021, 0RS022 PROFIRS Utwardzacz do szpachli**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: professional use.

Application of the substance / the mixture Hardening agent/ Curing agent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Inter Cars S.A.
ul. Powsińska 64,
02-903 Warszawa
Telefon: +48 22 714 10 70
Fax: +48 22 714 17 18
ic.diagnostyka@intercars.eu

Further information obtainable from: ic.diagnostyka@intercars.eu

1.4 Emergency telephone number: Tel. + 48 22 714 17 20; 112, czynny Pn-Pt 8:00-16:00

* **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02

Org. Perox. E H242 Heating may cause a fire.



GHS09

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02



GHS07



GHS09

(Contd. on page 2)

EN

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.11.2021

V- 2.0

Revision: 21.05.2018

Trade name: 0RS001, 0RS005, 0RS006, 0RS007, 0RS008, 0RS009, 0RS018, 0RS020, 0RS021, 0RS022 PROFIRS Utwardzacz do szpachli

(Contd. of page 1)

Signal word Warning**Hazard-determining components of labelling:**

dibenzoyl peroxide

Hazard statements

H242 Heating may cause a fire.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Risk of fire on contact with combustible substances or other substances effective in promoting the decomposition reaction.

Thermal decomposition with temperatures above 50°C (SADT).

Flammable.

Results of PBT and vPvB assessment**PBT:** Not applicable.**vPvB:** Not applicable.* **SECTION 3: Composition/information on ingredients****3.2 Mixtures****Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 94-36-0 EINECS: 202-327-6 Reg.nr.: 01-2119511472-50	dibenzoyl peroxide ⚠️⚠️ Org. Perox. B, H241; ⚠️ Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=10); ⚠️ Eye Irrit. 2, H319; Skin Sens. 1, H317	25-55%
CAS: 131-11-3 EINECS: 205-011-6 Reg.nr.: 01-2119437229-36	dimethyl phthalate substance with a Community workplace exposure limit	25-50%
CAS: 107-21-1 EINECS: 203-473-3 Reg.nr.: 02-2119752517-33 01-2119456816-28	ethanediol ⚠️ STOT RE 2, H373; ⚠️ Acute Tox. 4, H302	2.5-<10%

Additional information: For the wording of the listed hazard phrases refer to section 16.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.11.2021

V- 2.0

Revision: 21.05.2018

Trade name: 0RS001, 0RS005, 0RS006, 0RS007, 0RS008, 0RS009, 0RS018, 0RS020, 0RS021, 0RS022 PROFIRS Utwardzacz do szpachli

(Contd. of page 2)

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Take affected persons out of danger area and lay down.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

Avoid contact with the eyes and skin.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.11.2021

V- 2.0

Revision: 21.05.2018

Trade name: 0RS001, 0RS005, 0RS006, 0RS007, 0RS008, 0RS009, 0RS018, 0RS020, 0RS021, 0RS022 PROFIRS Utwardzacz do szpachli

(Contd. of page 3)

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Do not flush with water or aqueous cleansing agents.

Dispose of the material collected according to regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

* **SECTION 7: Handling and storage**

7.1 Precautions for safe handling

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Do not allow to enter sewers/ surface or ground water.

Keep apart from dirt, rust, chemicals, especially reducing substances, acids, alkaline solutions, amines and heavy metal compounds (such as accelerator, dessicative, metal soaps). Avoid naked flames, sparks, other ignition sources and sunlight.

Avoid any direct contact with accelerators.

Suitable materials: Stainless steel (DIN 1.4571), PVC, polyethylene, glass-lined apparatus.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Prevent impact and friction.

Fumes can combine with air to form an explosive mixture.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in the original receptacle.

Use only receptacles specifically permitted for this substance/product.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidising agents.

Further information about storage conditions:

Protect from frost.

Store in cool, dry conditions in well sealed receptacles.

Store receptacle in a well ventilated area.

Store under lock and key and out of the reach of children.

Maximum storage temperature: +25 °C

7.3 Specific end use(s) No further relevant information available.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.11.2021

V- 2.0

Revision: 21.05.2018

Trade name: 0RS001, 0RS005, 0RS006, 0RS007, 0RS008, 0RS009, 0RS018, 0RS020, 0RS021, 0RS022 PROFIRS Utwardzacz do szpachli

(Contd. of page 4)

* **SECTION 8: Exposure controls/personal protection**

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

94-36-0 dibenzoyl peroxide

WEL (Great Britain) Long-term value: 5 mg/m³

131-11-3 dimethyl phthalate

WEL (Great Britain) Short-term value: 10 mg/m³
Long-term value: 5 mg/m³

107-21-1 ethanediol

WEL (Great Britain) Short-term value: 104** mg/m³, 40** ppm
Long-term value: 10* 52** mg/m³, 20** ppm
Sk *particulate **vapour

IOELV (EU) Short-term value: 104 mg/m³, 40 ppm
Long-term value: 52 mg/m³, 20 ppm
Skin

Regulatory information

WEL (Great Britain): EH40/2020

IOELV (EU): (EU) 2019/1831

DNELs

131-11-3 dimethyl phthalate

Dermal DNEL 100 mg/kg bw/day (long-term - systemic effects, workers)

Inhalative DNEL 294 mg/m³ (long-term - systemic effects, workers)

PNECs

131-11-3 dimethyl phthalate

PNEC 0.192 mg/l (freshwater environment)

0.0192 mg/l (marine environment)

0.39 mg/l (intermittent releases)

4 mg/l (sewage treatment plants)

PNEC 1.403 mg/kg (freshwater sediment environment)

3.16 mg/kg (soil)

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see item 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Keep ignition sources away - Do not smoke.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.11.2021

V- 2.0

Revision: 21.05.2018

Trade name: 0RS001, 0RS005, 0RS006, 0RS007, 0RS008, 0RS009, 0RS018, 0RS020, 0RS021, 0RS022 PROFIRS Utwardzacz do szpachli

(Contd. of page 5)

Do not eat or drink while working.

Respiratory protection:

Filter A2/P2

Use suitable respiratory protective device in case of insufficient ventilation.

Hand protection



Protective gloves

Check the permeability prior to each renewed use of the glove.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation (EN 374).

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Synthetic rubber gloves

Neoprene gloves

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



Tightly sealed goggles

Body protection: Protective work clothing

* **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

General Information

Physical state	Fluid
Colour:	Red
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling range	Undetermined.
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	0.0 Vol %
Upper:	0.0 Vol %
Flash point:	>50 °C
Auto-ignition temperature:	Not determined.

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.11.2021

V- 2.0

Revision: 21.05.2018

Trade name: 0RS001, 0RS005, 0RS006, 0RS007, 0RS008, 0RS009, 0RS018, 0RS020, 0RS021, 0RS022 PROFIRS Utwardzacz do szpachli

(Contd. of page 6)

Decomposition temperature:	SADT = 50 °C
pH	Not applicable.
Viscosity:	
Kinematic viscosity	Not determined.
Dynamic:	Not determined.
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 °C:	<1 hPa
Density and/or relative density	
Density:	1.15-1.25 g/cm ³
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Pasty
Important information on protection of health and environment, and on safety.	
Explosive properties:	Product does not present an explosion hazard. Extreme risk of explosion by shock, friction, fire or other sources of ignition.
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Heating may cause a fire.
Corrosive to metals	Void
Desensitised explosives	Void

* **SECTION 10: Stability and reactivity**

10.1 Reactivity No decomposition if used according to specifications.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.11.2021

V- 2.0

Revision: 21.05.2018

Trade name: 0RS001, 0RS005, 0RS006, 0RS007, 0RS008, 0RS009, 0RS018, 0RS020, 0RS021, 0RS022 PROFIRS Utwardzacz do szpachli

(Contd. of page 7)

10.2 Chemical stability

Thermal decomposition with temperatures above 50°C (SADT).

Suitable materials: Stainless steel (DIN 1.4571), PVC, polyethylene, glass-lined apparatus.

10.3 Possibility of hazardous reactions

Fumes can combine with air to form an explosive mixture.

To avoid thermal decomposition do not overheat. Thermal decomposition or direct contact with numerous additives, such as reducing agents (i.e. amine accelerator), heavy metal compounds (in particular cobalt accelerators), acids and alkaline solutions, may lead to hazardous, autoaccelerating decomposition reactions, and possibly, to explosion or fire.

10.4 Conditions to avoid

Protect from heat and direct sunlight.

To avoid thermal decomposition do not overheat.

10.5 Incompatible materials:

Keep apart from dirt, rust, chemicals, especially reducing substances, acids, alkaline solutions, amines and heavy metal compounds (such as accelerator, dessicative, metal soaps). Avoid naked flames, sparks, other ignition sources and sunlight.

10.6 Hazardous decomposition products:

Danger of forming toxic pyrolysis products.

Formation of toxic gases is possible during heating or in case of fire.

*** SECTION 11: Toxicological information**

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

94-36-0 dibenzoyl peroxide

Oral	LD50	>5,000 mg/kg (rat)
Inhalative	LC50/4 h	24.3 mg/l (rat)

131-11-3 dimethyl phthalate

Oral	LD50	6,800 mg/kg (rat)
------	------	-------------------

107-21-1 ethanediol

Oral	LD50	5,840 mg/kg (rat)
Dermal	LD50	9,530 mg/kg (rabbit)

Primary irritant effect:

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Causes serious eye irritation.

Respiratory or skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.11.2021

V- 2.0

Revision: 21.05.2018

Trade name: 0RS001, 0RS005, 0RS006, 0RS007, 0RS008, 0RS009, 0RS018, 0RS020, 0RS021, 0RS022 PROFIRS Utwardzacz do szpachli

(Contd. of page 8)

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

* **SECTION 12: Ecological information**

12.1 Toxicity

Aquatic toxicity:

94-36-0 dibenzoyl peroxide

LC50/96 h | 0.0602 mg/l (Oncorhynchus mykiss)

EC50/48 h | 0.11 mg/l (Daphnia magna)

EC50/72 h | 0.0711 mg/l (Pseudokirchnerella subcapitata)

12.2 Persistence and degradability

94-36-0 dibenzoyl peroxide

Biodegradation | 68 % (readily biodegradable) (OECD 301 D, aerobic)

131-11-3 dimethyl phthalate

Biodegradation | 96-98 % (readily biodegradable) (OECD 301 E, 28 d)

12.3 Bioaccumulative potential

94-36-0 dibenzoyl peroxide

log Kow | 3.2 (OECD 117)

131-11-3 dimethyl phthalate

BCF | 57 (-)

log Pow | 1.56

12.4 Mobility in soil

131-11-3 dimethyl phthalate

log Koc | 1.57

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Additional ecological information:

General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.11.2021

V- 2.0

Revision: 21.05.2018

Trade name: 0RS001, 0RS005, 0RS006, 0RS007, 0RS008, 0RS009, 0RS018, 0RS020, 0RS021, 0RS022 PROFIRS Utwardzacz do szpachli

(Contd. of page 9)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

16 05 06*	laboratory chemicals, consisting of or containing hazardous substances, including mixtures of laboratory chemicals
-----------	--

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

* **SECTION 14: Transport information**

14.1 UN number or ID number
ADR, IMDG, IATA

UN3108

14.2 UN proper shipping name

ADR
IMDG

3108 ORGANIC PEROXIDE TYPE E, SOLID
ORGANIC PEROXIDE TYPE E, SOLID,
MARINE POLLUTANT
ORGANIC PEROXIDE TYPE E, SOLID

IATA

14.3 Transport hazard class(es)

ADR, IMDG



Class
Label

5.2
5.2

IATA



Class
Label

5.2
5.2

14.4 Packing group

ADR

Void

14.5 Environmental hazards:

Marine pollutant (IMDG):

Environmentally hazardous substance, liquid

Yes

Symbol (fish and tree)

Special marking (ADR):

Symbol (fish and tree)

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.11.2021

V- 2.0

Revision: 21.05.2018

Trade name: 0RS001, 0RS005, 0RS006, 0RS007, 0RS008, 0RS009, 0RS018, 0RS020, 0RS021, 0RS022 PROFIRS Utwardzacz do szpachli

(Contd. of page 10)

14.6 Special precautions for user	Warning: Organic peroxides.
EMS Number:	F-J,S-R
Stowage Category	D
Stowage Code	SW1 Protected from sources of heat.
Segregation Code	SG35 Stow "separated from" SGG1-acids SG36 Stow "separated from" SGG18-alkalis.
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	500 g
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	500 g
UN "Model Regulation":	UN 3108 ORGANIC PEROXIDE TYPE E, SOLID, 5.2

* **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category

P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES

E1 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.11.2021

V- 2.0

Revision: 21.05.2018

Trade name: 0RS001, 0RS005, 0RS006, 0RS007, 0RS008, 0RS009, 0RS018, 0RS020, 0RS021, 0RS022 PROFIRS Utwardzacz do szpachli

(Contd. of page 11)

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

National regulations:

Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

*** SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H241 Heating may cause a fire or explosion.

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008

Organic peroxides

On basis of test data

Serious eye damage/eye irritation

Skin sensitisation

Hazardous to the aquatic environment - short-term (acute) aquatic hazard

Hazardous to the aquatic environment - long-term (chronic) aquatic hazard

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Version number of previous version: 1.9

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Org. Perox. B: Organic peroxides – Type B

Org. Perox. E: Organic peroxides – Type E/F

Acute Tox. 4: Acute toxicity – Category 4

(Contd. on page 13)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.11.2021

V- 2.0

Revision: 21.05.2018

Trade name: ORS001, ORS005, ORS006, ORS007, ORS008, ORS009, ORS018, ORS020, ORS021, ORS022 PROFIRS Utwardzacz do szpachli

(Contd. of page 12)

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Sensitisation - Skin. Hazard Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - Acute Hazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Sources European Chemicals Agency, <http://echa.europa.eu/>

*** Data compared to the previous version altered.**

EN —