ECT	TON 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
.1	Product identifier: 0RS123 SZPACHLÓWKA Z WŁÓKNEM SZKLANYM
	Other means of identification:
	UFI: KKD1-N10H-Q00P-497J
2	Relevant identified uses of the substance or mixture and uses advised against:
	Relevant uses: Car repair; filler for joints, cracks, etc For professional users only.
	Uses advised against: All uses not specified in this section or in section 7.3
3	Details of the supplier of the safety data sheet:
	Troton Sp. z o.o. Ząbrowo 14A 78-120 Gościno - Zachodniopomorskie - Polska Phone: +48 94 35 123 94 - Fax: +48 94 35 126 22 troton@troton.com.pl www.troton.pl / www.troton.eu
.4	Emergency telephone number: (8am-4pm)+48 094 35 123 94; 112
	TON 2: HAZARDS IDENTIFICATION
.1	Classification of the substance or mixture:
	CLP Regulation (EC) No 1272/2008:
	Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008. Eye Irrit. 2: Eye irritation, Category 2, H319
.2	Flam. Liq. 3: Flammable liquids, Category 3, H226 Repr. 2: Reproductive toxicity, Category 2, H361d Skin Irrit. 2: Skin irritation, Category 2, H315 STOT RE 1: Specific target organ toxicity, repeated exposure, Category 1, H372 Label elements:
	CLP Regulation (EC) No 1272/2008:
	Danger
	Hazard statements:
	Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Liq. 3: H226 - Flammable liquid and vapour. Repr. 2: H361d - Suspected of damaging the unborn child. Skin Irrit. 2: H315 - Causes skin irritation. STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure.
	Precautionary statements:
	<ul> <li>P201: Obtain special instructions before use.</li> <li>P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</li> <li>P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.</li> <li>P302+P352: IF ON SKIN: Wash with plenty of water.</li> <li>P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to</li> </ul>
	<ul> <li>do. Continue rinsing.</li> <li>P308+P313: IF exposed or concerned: Get medical advice/attention.</li> <li>P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.</li> </ul>
	Substances that contribute to the classification
2	styrene Other hazards:
3	
	Product fails to meet PBT/vPvB criteria

Printing: 20/10/2021	Date of compilation: 20/10/2021	Version: 1
----------------------	---------------------------------	------------

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS 3.1 Substance: Non-applicable 3.2 Mixture: Chemical description: Mixture composed of chemical products Components: In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains: Identification Concentration

	Identification		Chemical hame/Classification		Concentration	
CAS:	100-42-5	styrene <sup>(1)</sup>		ATP ATP06		
EC: Index: REACH	202-851-5 601-026-00-0 : 01-2119457861-32- XXXX		Acute Tox. 4: H332; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 1: H372 - Danger	() 🔅 🚸	10 - <25 %	

(1) Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

# SECTION 4: FIRST AID MEASURES

### 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

#### By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

#### By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

#### By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

#### By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

# 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

#### 4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

#### SECTION 5: FIREFIGHTING MEASURES

#### 5.1 Extinguishing media:

#### Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO2).

#### Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

#### 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

# Printing: 20/10/2021 Date of compilation: 20/10/2021 Version: 1

#### SECTION 5: FIREFIGHTING MEASURES (continued)

#### 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

#### Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures:

#### For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

# For emergency responders:

See section 8.

#### 6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

### 6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

### 6.4 Reference to other sections:

See sections 8 and 13.

# SECTION 7: HANDLING AND STORAGE

#### 7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in designated areas that comply with the necessary safety conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to small amounts only. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

Printing	20/10/2021	Date of compilation: 20/10/2021	Version: 1			
SEC	SECTION 7: HANDLING AND STORAGE (continued)					
7.2	Conditions for	safe storage, including any incom	ipatibilities:			
	A Technical me	easures for storage				
	Minimum Te	mp.: 15 °C				
	Maximum Te	emp.: 25 °C				
	Maximum tin	ne: 12 Months				
	B General cond	ditions for storage				

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

#### 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

There are no occupational exposure limits for the substances contained in the product

### DNEL (Workers):

		Short e	xposure	Long ex	xposure
Identification		Systemic	Local	Systemic	Local
styrene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 100-42-5	Dermal	Non-applicable	Non-applicable	406 mg/kg	Non-applicable
EC: 202-851-5	Inhalation	289 mg/m <sup>3</sup>	306 mg/m <sup>3</sup>	85 mg/m³	Non-applicable

#### DNEL (General population):

		Short e	xposure	Long ex	kposure
Identification		Systemic	Local	Systemic	Local
styrene	Oral	Non-applicable	Non-applicable	2,1 mg/kg	Non-applicable
CAS: 100-42-5	Dermal	Non-applicable	Non-applicable	343 mg/kg	Non-applicable
EC: 202-851-5	Inhalation	174,25 mg/m <sup>3</sup>	182,75 mg/m <sup>3</sup>	10,2 mg/m <sup>3</sup>	Non-applicable

#### PNEC:

Identification				
styrene	STP	5 mg/L	Fresh water	0,028 mg/L
CAS: 100-42-5	Soil	0,2 mg/kg	Marine water	0,014 mg/L
EC: 202-851-5	Intermittent	0,04 mg/L	Sediment (Fresh water)	0,614 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,307 mg/kg

### 8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the occupational exposure limits. In case of using personal protective equipment it should have CE marking in accordance with Directive 2016/425/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

#### B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

Mandatory and Interest of several substances, the resistance of the glove material can not be calculated in adva tata reliability and has therefore to be checked prior to the application.D. Cuclar and facial protectionThe several substances, the resistance of the glove material can not be calculated in adva tata reliability and has therefore to be checked prior to the application.D. Cuclar and facial protectionFace shieldCorr of the several substances, the resistance of the glove material can not be calculated in adva tata reliability and has therefore to be checked prior to the application.PictogramPPELabellingCEN StandardRemarks (Be 2002) EN 166:2002 EN 166:2002 EN 166:2002 EN 166:2002 EN 166:2002 EN 166:2002 EN 160:2002 EN 160:2002 EN 160:2002 EN 160:2002 EN 160:2002 EN 160:2002 EN 160:2002 EN 160:2002 EN 160:2002 EN 150:4007:2018Clean daily and disinfect periodically at the manufacturer's instructions. Use risk of splashing.PictogramPPELabellingCEN StandardRemarks EN 150:4007:2018Clean daily and disinfect periodically at the manufacturer's instructions. Use risk of splashing.PictogramPPELabellingCEN StandardRemarks EN 150:4007:2018Clean daily and disinfect periodically at the manufacturer's instructions. Use risk of an attribute and hei fireproof propertiesEn 1149-12,3 EN 150:32021 EN 150:32021 EN 150:320231 EN 150:320231 EN 150:320231 EN 150:32024 EN 150:320231 EN 150:320245:2011 EN 150:320245:2011 EN 130321:2019Cen candards resident and resident and resident at the resi					Version		mpilation: 20/10			g: 20/1
Production         PPE         Labelling         CEN Standard         Remarks           Windstory hard         Chemical productible gloves min, Thickness: 0.062 nm)         Ex 100         Relace the gloves at any sign of de markstorogic lines: 0.062 nm)           As the product is a mixture of several substances, the resistance of the glove material can not be calculated in adva total reliability and has therefore to be checked prior to the application.         Cen daily and testing the markstore field in the product is a mixture of several substances, the resistance of the glove material can not be calculated in adva total reliability and has therefore to be checked prior to the application.           D: Ocular and facial protection         Face shield         Cen Standard         Remarks           Windstory face         Disposable dothing for protection against chemical risk, with antistatic and heat         Cen Standard         Remarks           Windstory fort         Disposable dothing for protection against chemical risk, with antistatic and heat         Cen T II         EN 103/382-1201         For profesional use only. Cean place tothing risket from points     <				continued)	ION (	AL PROTECT				
Image: Constraint of the productive gives the productive production of the product is a mixture of several substances, the resistance of the glove material can not be calculated in adva total reliability and has therefore to be checked prior to the application.         Evaluation of the product is a mixture of several substances, the resistance of the glove material can not be calculated in adva total reliability and has therefore to be checked prior to the application.           Decision of the product is a mixture of several substances, the resistance of the glove material can not be calculated in adva total reliability and has therefore to be checked prior to the application.         Cent and facial protection           Productory free product is a mixture of several substances, the resistance of the glove material can not be calculated in adva total reliability and has therefore to be checked prior to the application.         Cent and facial protection           Productory free production prior for protection         Protection         Evaluate the product is an instance of the glove material can not be calculated in adva total protection.           E. Body protection         Protection         Evaluate the product is a mixture of several substance of the glove material can not be calculated in adva total protection against chemical prise themical prise total protection against chemical prise total protection against chemical prise total prise themical prise total prise themical prise total prise themical prise total prise themical mission and prise total prise themical prise total prise themical prise total prise themical prise total prise themical prise total prise total prise total prise themical prise total pri		Pomarke		CEN Standard		Labolling		n for the	· ·	C
total reliability and has therefore to be checked prior to the application."         PE cogram PE colspan="2">CEN Standard Remarks         En Ideogram PE colspan="2">CEN Standard Remarks         CEN Standard Remarks         CEN Standard disinfect periodically.         Mandatory for protection         Decemarks         CEN Standard Remarks         Find CEN Standard Remarks	eterioration.	ace the gloves at any sign of deteriora	Repla		EN	CAT III	al protective gloves : Linear low-density thylene (LLDPE), rough time: > 480	(Material: polyet Breakthr	Mandatory hand	
Pictogram         PPE         Labelling         CEN Standard         Remarks           Windstary frace protection         Face shield         CEN         Bit 167:2002 EN 1157:2002 EN 150:4007:2018         Clean daily and disinfect periodically it the manufacturer's instructions. Use risk of splashing.           E.         Body protection         En Idea (Internet instructions)         En Idea (Inter	ance with	not be calculated in advance w	rial can				erefore to be che	d has the	otal reliability and	
Image: Second and the component of the product of		Remarks		CEN Standard		Labelling				2.
Precogram         PPE         Labelling         CEN Standard         Remarks           With regard to Disposable clothing for protection against chemical risk, with antistatic and freproof properties         Image: CEN Standard         For professional use only. Clean pe according to the manufacturer's in EN 150 6529:2013 EN 150 6529:2013 EN 150 6529:2013 EN 150 6529:2013 EN 150 6529:2013 EN 150 6529:2013 EN 150 1388:2013         For professional use only. Clean pe according to the manufacturer's in Protection against chemical resistant properties           Safety footware for protection against chemical resistant properties         EM 50 13287:2013 EN 150 20345:2011 EN 150 20345:2011 EN 150 20345:2011         Replace boots at any sign of deter           F Additional emergency measures         Standards         Emergency measure         Standards           Emergency measure         Standards         Emergency measure         Standards           Environmental exposure controls:         Iso 3864-1:2011, ISO 3864-4:2011         Image: Environment it is recommended to avoid environ spillage of both the product and its container. For additional information see subsection 7.1.D Volatile organic compounds           With regard to Directive 2010/75/EU, this product has the following characteristics:         V.O.C. (Supply):         13,38 % weight           V.O.C. density at 20 °C:         46 kg/m³ (46 g/L) Average carbon number:         8 Average molecular weight:         104,2 g/mol		anufacturer's instructions. Use if the		EN 167:2002 EN 168:2002	E		Face shield	F		
Image: Note of the production against chemical fireproof properties       Image: Note of the production against chemical fireproof properties       Image: Note of the production against chemical fireproof properties       Image: Note of the production against chemical fireproof properties       Image: Note of the production against chemical fireproof properties       Image: Note of the production against chemical fireproof properties       Image: Note of the production against chemical fireproof properties       Image: Note of the production against chemical fireproof properties       Image: Note of the production against chemical fireproof properties       Image: Note of the production against chemical fireproof properties       Image: Note of the production against chemical fireproof properties       Image: Note of the production against chemical fireproof properties       Image: Note of the production against chemical fireproof properties       Image: Note of the production against chemical fireproof properties       Image: Note of the production against chemical fireproof properties       Image: Note of the production against chemical fireproof properties       Image: Note of the production against chemical fireproof properties       Image: Note of the production against chemical fireproof properties       Image: Note of the production against chemical fireproof properties       Image: Note of the production against chemical fireproof properties       Image: Note of the production against chemical fireproof properties       Image: Note of the production against chemical fireproof properties       Image: Note of the production against chemical fireproof properties       Image: Note of the production against chemical fireproof properties       Image: Note of the prop									Body protection	E
Image: Complete body protection against chemical body protection against chemical freproof properties       Image: Complete body protection against chemical free body protection against chemical free body protection       Image: Complete body protection against chemical free body protection for the protection against chemical free body protection against chemical free body protection for the protection of the environment it is recommended to avoid environ spillage of both the product and its container. For additional information see subsection 7.1.D <t< td=""><td></td><td>Remarks</td><td></td><td>CEN Standard</td><td></td><td>Labelling</td><td>PPE</td><td></td><td>Pictogram</td><td></td></t<>		Remarks		CEN Standard		Labelling	PPE		Pictogram	
Image: Non-Additional State Controls       Image: Standards for the protection against chemical resistant properties       Image: Standards for the protection state and heat resistant properties       Image: Standards for the protection state and protection state and protection state and protection       Replace boots at any sign of deter         F Additional emergency measures       Image: Standards for the protection state and protection protection protection state and protection protectin protectin protection protection protection protecti		For professional use only. Clean periodicallaccording to the manufacturer's instruction		EN 13034:2005+A1:2009 EN ISO 13982- 1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013			Disposable clothing for protection against chemical risks, with antistatic and			
F       Additional emergency measures         Emergency measure       Standards       Emergency measure       Standards         Image: Emergency shower       Iso 3864-1:2011, ISO 3864-4:2011       Image: Emergency measure       Standards         Environmental exposure controls:       Iso ascordance with the community legislation for the protection of the environment it is recommended to avoid environ spillage of both the product and its container. For additional information see subsection 7.1.D       Volatile organic compounds:         With regard to Directive 2010/75/EU, this product has the following characteristics:       V.O.C. (Supply):       13,38 % weight         V.O.C. density at 20 °C:       46 kg/m³ (46 g/L)       Average molecular weight:       104,2 g/mol	rioration.	place boots at any sign of deterioratic	Replace boots at any sign of deterio		EN ISO 20345:2		on against chemical antistatic and heat	Mandatory foot protection against cheminisk, with antistatic and hereistant properties		
ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011       Image: Dist of the second seco							asures	ency mea	•	F
Image: Non-ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011       Image: DIN 12 899 ISO 3864-1:2011, ISO 3864         Image: Discretion of the service of		Standards	Jre	Emergency measur		andards	St	asure	Emergency mea	
In accordance with the community legislation for the protection of the environment it is recommended to avoid environ spillage of both the product and its container. For additional information see subsection 7.1.D <b>Volatile organic compounds:</b> With regard to Directive 2010/75/EU, this product has the following characteristics: V.O.C. (Supply): 13,38 % weight V.O.C. density at 20 °C: 46 kg/m <sup>3</sup> (46 g/L) Average carbon number: 8 Average molecular weight: 104,2 g/mol	54-4:2011	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:20	IS					ower	Emergency sho	
V.O.C. density at 20 °C:46 kg/m³ (46 g/L)Average carbon number:8Average molecular weight:104,2 g/mol	ımental	nmended to avoid environment	<b>Environmental exposure controls:</b> In accordance with the community legislation for the protection of the environment it is recommended to avoid environmen spillage of both the product and its container. For additional information see subsection 7.1.D <b>Volatile organic compounds:</b>							
Average carbon number:8Average molecular weight:104,2 g/mol						% weight	13,38		/.O.C. (Supply):	
Average molecular weight: 104,2 g/mol						/m³ (46 g/L)	5		-	
						, .			-	
						g/mol	:: 104,2	r weight	verage molecula	
						EDTIEC				
L Information on basic physical and chemical properties: For complete information see the product datasheet.					s:	cal propertie	sical and chemi	sic phys	rmation on bas	<b>Inf</b> For
Appearance: Physical state at 20 °C: Liquid					id	Lieu		c٠		

 $\ensuremath{^*\text{Not}}$  relevant due to the nature of the product, not providing information property of its hazards.

20/10/2021 Date of compilation: 20/10/2021	Version: 1	
ON 9: PHYSICAL AND CHEMICAL PROPERTIE	S (continued)	
Appearance:	Viscous	
Colour:	Greenish	
Odour:	Characteristic	
Odour threshold:	Non-applicable *	
Volatility:		
Boiling point at atmospheric pressure:	145 °C	
Vapour pressure at 20 °C:	622 Pa	
Vapour pressure at 50 °C:	3297,17 Pa (3,3 kPa)	
Evaporation rate at 20 °C:	Non-applicable *	
Product description:		
Density at 20 °C:	1820 kg/m <sup>3</sup>	
Relative density at 20 °C:	1,743	
Dynamic viscosity at 20 °C:	Non-applicable *	
Kinematic viscosity at 20 °C:	Non-applicable *	
Kinematic viscosity at 40 °C:	>20,5 mm²/s	
Concentration:	Non-applicable *	
pH:	Non-applicable *	
Vapour density at 20 °C:	Non-applicable *	
Partition coefficient n-octanol/water 20 °C:	Non-applicable *	
Solubility in water at 20 °C:	Non-applicable *	
Solubility properties:	Non-applicable *	
Decomposition temperature:	Non-applicable *	
Melting point/freezing point:	Non-applicable *	
Flammability:		
Flash Point:	32 °C	
Flammability (solid, gas):	Non-applicable *	
Autoignition temperature:	490 °C	
Lower flammability limit:	Not available	
Upper flammability limit:	Not available	
Particle characteristics:		
Median equivalent diameter:	Non-applicable	
Other information:		
Information with regard to physical hazard clas	ises:	
Explosive properties:	Non-applicable *	
Oxidising properties:	Non-applicable *	
Corrosive to metals:	Non-applicable *	
Heat of combustion:	Non-applicable *	
Aerosols-total percentage (by mass) of flammable components:	Non-applicable *	
Other safety characteristics:		
Surface tension at 20 °C:	Non-applicable *	
Refraction index:	Non-applicable *	
*Not relevant due to the nature of the product, not providing info	rmation property of its hazards.	

SECTION 10: STABILITY AND REACTIVITY

10.1	Reactivity:					
	No hazardous reactio	ons are expe	ected because the p	roduct is stable under reco	mmended storage conditi	ions. See section 7.
10.2 Chemical stability:						
	Chemically stable und	der the con	ditions of storage, h	andling and use.		
10.3 Possibility of hazardous reactions:						
under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.						
	Under the specified c	conditions, ł		that lead to excessive tem	peratures or pressure are	not expected.
.0.4	Under the specified c Conditions to avoid	•		that lead to excessive tem	peratures or pressure are	e not expected.
.0.4	•	d:	hazardous reactions		peratures or pressure are	not expected.
.0.4	Conditions to avoid	d: ng and stora	hazardous reactions		peratures or pressure are Sunlight	not expected.
.0.4	Conditions to avoid Applicable for handlin	d: ng and stora	hazardous reactions age at room temper	ature:		
	Conditions to avoid Applicable for handlin Shock and friction	d: ng and stora	hazardous reactions age at room temper Contact with air	ature: Increase in temperature	Sunlight	Humidity
10.4	Conditions to avoid Applicable for handlin Shock and friction Not applicable	d: ng and stora	hazardous reactions age at room temper Contact with air	ature: Increase in temperature	Sunlight	Humidity

### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

# SECTION 11: TOXICOLOGICAL INFORMATION

### **11.1** Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

#### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
  - Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
  - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
  - Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
  - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Produces skin inflammation.
  - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
    - IARC: styrene (2A); Talc (3)
  - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
  - Reproductive toxicity: Suspected of damaging the unborn child.
- E- Sensitizing effects:
  - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
  - Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Printing: 20/10/20	D21 Date of compilation: 20/10/2021 Version: 1
SECTION 11:	: TOXICOLOGICAL INFORMATION (continued)
this e	ed on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for effect. For more information see section 3. cific target organ toxicity (STOT)-repeated exposure:
inclu - SI dang	pecific target organ toxicity (STOT)-repeated exposure: Serious health effects in the case of prolonged consumption, iding death, serious functional disorders or morphological changes of toxicological importance. kin: Based on available data, the classification criteria are not met, as it does not contain substances classified as gerous for this effect. For more information see section 3. ration hazard:
this e	ed on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for effect. For more information see section 3. <b>nformation:</b>

Non-applicable

### Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
styrene	LD50 oral	>2000 mg/kg	
CAS: 100-42-5	LD50 dermal	>2000 mg/kg	
EC: 202-851-5	LC50 inhalation	12 mg/L (4 h)	Rat

# SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

### 12.1 Toxicity:

Not available

# 12.2 Persistence and degradability:

Not available

### **12.3** Bioaccumulative potential:

Not available

### 12.4 Mobility in soil:

Identification	Absorp	Absorption/desorption		ility
styrene	Кос	Non-applicable	Henry	Non-applicable
CAS: 100-42-5	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 202-851-5	Surface tension	3,21E-2 N/m (25 °C)	Moist soil	Non-applicable
Begulte of DPT and vDvP accomments				

#### 12.5 Results of PBT and vPvB assessment:

# Printing: 20/10/2021 Date of compilation: 20/10/2021 Version: 1

# SECTION 12: ECOLOGICAL INFORMATION (continued)

# Product fails to meet PBT/vPvB criteria

# 12.6 Other adverse effects:

Not described

# SECTION 13: DISPOSAL CONSIDERATIONS

#### **13.1 Waste treatment methods:**

Code	Description	Waste class (Regulation (EU) No 1357/2014)
	waste paint and varnish containing organic solvents or other hazardous substances packaging containing residues of or contaminated by hazardous substances	Dangerous

#### Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP10 Toxic for reproduction, HP4 Irritant — skin irritation and eye damage

#### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

#### **Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

# SECTION 14: TRANSPORT INFORMATION

with regard to		1 and RID 2021:	
	14.1	UN number:	UN3269
	14.2	UN proper shipping name:	POLYESTER RESIN KIT, liquid base material
	14.3	Transport hazard class(es):	3
$\langle - \rangle$		Labels:	3
	14.4	Packing group:	III
3	14.5	Environmental hazards:	No
	14.6	Special precautions for user	
		Special regulations:	236, 340
		Tunnel restriction code:	E
		Physico-Chemical properties:	see section 9
		Limited quantities:	5 L
	14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable
Transport of	dangero	us goods by sea:	

Printing: 20/10/2021	Date o	of compilation: 20/10/2021	Version: 1
SECTION 14: TRANSP	PORT 1	INFORMATION (continued)	
3	14.2 14.3 14.4 14.5	UN number: UN proper shipping name: Transport hazard class(es): Labels: Packing group: Marine pollutant: Special precautions for user Special regulations: EmS Codes: Physico-Chemical properties: Limited quantities: Segregation group:	UN3269 POLYESTER RESIN KIT, liquid base material 3 3 III No 340, 236 F-E, S-D see section 9 5 L Non-applicable
		Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable
With regard to IA	-	us goods by air:	
With regard to IA	14.1 14.2	UN number: UN proper shipping name: Transport hazard class(es):	UN3269 POLYESTER RESIN KIT, liquid base material 3
3	14.4 14.5	Labels: Packing group: Environmental hazards: Special precautions for user Physico-Chemical properties:	3 III No see section 9
	14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable

# SECTION 15: REGULATORY INFORMATION

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

# Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000
Limitations to commercialization and the use of cortain dangerous substances and mixtures (Appex V/II DEACH			

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):

Shall not be used in:

--ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

-games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

# Other legislation:

Printing: 20/10/2021 Date of compilation: 20/10/2021 Version: 1
SECTION 15: REGULATORY INFORMATION (continued)
The product could be affected by sectorial legislation
15.2 Chemical safety assessment:
The supplier has not carried out evaluation of chemical safety.
The supplier has not carried out evaluation of chemical safety.
SECTION 16: OTHER INFORMATION
Legislation related to safety data sheets: The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830).
Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:
Non-applicable Texts of the legislative phrases mentioned in section 2:
H315: Causes skin irritation.
H372: Causes damage to organs through prolonged or repeated exposure. H361d: Suspected of damaging the unborn child. H226: Flammable liquid and vapour.
H319: Causes serious eye irritation. Texts of the legislative phrases mentioned in section 3:
The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3
CLP Regulation (EC) No 1272/2008:
Acute Tox. 4: H332 - Harmful if inhaled. Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Liq. 3: H226 - Flammable liquid and vapour. Repr. 2: H361d - Suspected of damaging the unborn child. Skin Irrit. 2: H315 - Causes skin irritation. STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure.
Classification procedure:
Skin Irrit. 2: Calculation method STOT RE 1: Calculation method Repr. 2: Calculation method Flam. Liq. 3: Calculation method (2.6.4.3) Eye Irrit. 2: Calculation method
Advice related to training:
Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. <b>Principal bibliographical sources:</b>
http://echa.europa.eu http://eur-lex.europa.eu
Abbreviations and acronyms: ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5day biochemical oxygen demand
BCF: Bioconcentration factor LD50: Lethal Dose 50
LC50: Lethal Concentration 50 EC50: Effective concentration 50 LogPOW: Octanolwater partition coefficient
Koc: Partition coefficient of organic carbon
UFI: unique formula identifier IARC: International Agency for Research on Cancer
The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.