

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation

ORS128 UTWARDZACZ DO PODKŁADU WYSOKOWYPEŁNIAJĄCEGO

Printing: 20/10/2021

Date of compilation: 20/10/2021

Version: 1

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: ORS128 UTWARDZACZ DO PODKŁADU WYSOKOWYPEŁNIAJĄCEGO

Other means of identification:

UFI: YOC5-D18M-G00E-ER0H

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Car repair; base for coatings. For professional users only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Troton Sp. z o.o.

Ząbrowo 14A

78-120 Gościno - Zachodniopomorskie - Polska

Phone: +48 94 35 123 94 - Fax: +48 94 35 126 22

troton@troton.com.pl

www.troton.pl / www.troton.eu

1.4 Emergency telephone number: (8am-4pm)+48 094 35 123 94; 112

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Acute Tox. 4: Acute inhalation toxicity, Category 4, H332

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

Eye Irrit. 2: Eye irritation, Category 2, H319

Flam. Liq. 3: Flammable liquids, Category 3, H226

Skin Irrit. 2: Skin irritation, Category 2, H315

Skin Sens. 1: Sensitisation, skin, Category 1, H317

STOT RE 2: Specific target organ toxicity if swallowed, repeated exposure, Category 2, H373

STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Warning



Hazard statements:

Acute Tox. 4: H332 - Harmful if inhaled.

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).

STOT SE 3: H335 - May cause respiratory irritation.

Precautionary statements:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.

P302+P352: IF ON SKIN: Wash with plenty of water.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

Supplementary information:

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation

ORS128 UTWARDZACZ DO PODKŁADU WYSOKOWYPEŁNIAJĄCEGO

Printing: 20/10/2021

Date of compilation: 20/10/2021

Version: 1

SECTION 2: HAZARDS IDENTIFICATION (continued)

EUH204: Contains isocyanates. May produce an allergic reaction.

Substances that contribute to the classification

Xylene; Hexamethylene diisocyanate, oligomers; Hydrocarbons, C9, aromatics; Ethylbenzene

Additional Labelling (Annex XVII, REACH):

As from 24 August 2023 adequate training is required before industrial or professional use.

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of chemical products

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

| Identification | Chemical name/Classification | Concentration |
|-------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32-XXXX | Xylene⁽¹⁾ Self-classified | 25 - <50 % |
| | Regulation 1272/2008 Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger | |
| CAS: 28182-81-2 EC: 931-274-8 Index: Non-applicable REACH: 01-2119485796-17-XXXX | Hexamethylene diisocyanate, oligomers⁽¹⁾ Self-classified | 25 - <50 % |
| | Regulation 1272/2008 Acute Tox. 4: H332; Skin Sens. 1: H317; STOT SE 3: H335 - Warning | |
| CAS: 108-65-6 EC: 203-603-9 Index: 607-195-00-7 REACH: 01-2119475791-29-XXXX | 2-methoxy-1-methylethyl acetate⁽²⁾ ATP ATP01 | 10 - <25 % |
| | Regulation 1272/2008 Flam. Liq. 3: H226 - Warning | |
| CAS: 64742-95-6 EC: 918-668-5 Index: Non-applicable REACH: 01-2119455851-35-XXXX | Hydrocarbons, C9, aromatics⁽¹⁾ Self-classified | 5 - <10 % |
| | Regulation 1272/2008 Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; STOT SE 3: H336; EUH066 - Danger | |
| CAS: 100-41-4 EC: 202-849-4 Index: 601-023-00-4 REACH: 01-2119489370-35-XXXX | Ethylbenzene⁽¹⁾ ATP ATP06 | 1 - <2,5 % |
| | Regulation 1272/2008 Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger | |
| CAS: 822-06-0 EC: 212-485-8 Index: 615-011-00-1 REACH: 01-2119457571-37-XXXX | Hexamethylene-di-isocyanate⁽¹⁾ ATP CLP00 | <1 % |
| | Regulation 1272/2008 Acute Tox. 3: H331; Eye Irrit. 2: H319; Resp. Sens. 1: H334; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT SE 3: H335 - Danger | |

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

⁽²⁾ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation

ORS128 UTWARDZACZ DO PODKŁADU WYSOKOWYPEŁNIAJĄCEGO

Printing: 20/10/2021

Date of compilation: 20/10/2021

Version: 1

SECTION 4: FIRST AID MEASURES (continued)

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation

ORS128 UTWARDZACZ DO PODKŁADU WYSOKOWYPEŁNIAJĄCEGO

Printing: 20/10/2021

Date of compilation: 20/10/2021

Version: 1

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 15 °C

Maximum Temp.: 25 °C

Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

| Identification | Occupational exposure limits | | |
|---------------------------------|------------------------------|--------------|-----------------------|
| | IOELV (8h) | IOELV (STEL) | |
| Xylene | 50 ppm | | 221 mg/m ³ |
| CAS: 1330-20-7 EC: 215-535-7 | 100 ppm | | 442 mg/m ³ |
| 2-methoxy-1-methylethyl acetate | 50 ppm | | 275 mg/m ³ |
| | 100 ppm | | 550 mg/m ³ |
| CAS: 108-65-6 EC: 203-603-9 | 100 ppm | | 442 mg/m ³ |
| Ethylbenzene | 100 ppm | | 442 mg/m ³ |
| | 200 ppm | | 884 mg/m ³ |
| CAS: 100-41-4 EC: 202-849-4 | | | |

DNEL (Workers):

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation

ORS128 UTWARDZACZ DO PODKŁADU WYSOKOWYPEŁNIAJĄCEGO

Printing: 20/10/2021

Date of compilation: 20/10/2021

Version: 1

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

| Identification | | Short exposure | | Long exposure | |
|---------------------------------------------------------------------------|------------|-----------------------|------------------------|-----------------------|-------------------------|
| | | Systemic | Local | Systemic | Local |
| Xylene CAS: 1330-20-7 EC: 215-535-7 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 212 mg/kg | Non-applicable |
| | Inhalation | 442 mg/m ³ | 442 mg/m ³ | 221 mg/m ³ | 221 mg/m ³ |
| Hexamethylene diisocyanate, oligomers CAS: 28182-81-2 EC: 931-274-8 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Inhalation | Non-applicable | 1 mg/m ³ | Non-applicable | 0,5 mg/m ³ |
| 2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 796 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | 550 mg/m ³ | 275 mg/m ³ | Non-applicable |
| Hydrocarbons, C9, aromatics CAS: 64742-95-6 EC: 918-668-5 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 25 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 150 mg/m ³ | Non-applicable |
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 180 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | 293 mg/m ³ | 77 mg/m ³ | Non-applicable |
| Hexamethylene-di-isocyanate CAS: 822-06-0 EC: 212-485-8 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Inhalation | Non-applicable | 0,07 mg/m ³ | Non-applicable | 0,035 mg/m ³ |

DNEL (General population):

| Identification | | Short exposure | | Long exposure | |
|-------------------------------------------------------------------|------------|-----------------------|-----------------------|------------------------|------------------------|
| | | Systemic | Local | Systemic | Local |
| Xylene CAS: 1330-20-7 EC: 215-535-7 | Oral | Non-applicable | Non-applicable | 12,5 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 125 mg/kg | Non-applicable |
| | Inhalation | 260 mg/m ³ | 260 mg/m ³ | 65,3 mg/m ³ | 65,3 mg/m ³ |
| 2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9 | Oral | Non-applicable | Non-applicable | 36 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 320 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 33 mg/m ³ | 33 mg/m ³ |
| Hydrocarbons, C9, aromatics CAS: 64742-95-6 EC: 918-668-5 | Oral | Non-applicable | Non-applicable | 11 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 11 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 32 mg/m ³ | Non-applicable |
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | Oral | Non-applicable | Non-applicable | 1,6 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 15 mg/m ³ | Non-applicable |

PNEC:

| Identification | | | | | |
|---------------------------------------------------------------------------|--------------|----------------|-------------------------|--------------|--|
| Xylene CAS: 1330-20-7 EC: 215-535-7 | STP | 6,58 mg/L | Fresh water | 0,327 mg/L | |
| | Soil | 2,31 mg/kg | Marine water | 0,327 mg/L | |
| | Intermittent | 0,327 mg/L | Sediment (Fresh water) | 12,46 mg/kg | |
| | Oral | Non-applicable | Sediment (Marine water) | 12,46 mg/kg | |
| Hexamethylene diisocyanate, oligomers CAS: 28182-81-2 EC: 931-274-8 | STP | 88 mg/L | Fresh water | 0,127 mg/L | |
| | Soil | 53183 mg/kg | Marine water | 0,013 mg/L | |
| | Intermittent | 1,27 mg/L | Sediment (Fresh water) | 266701 mg/kg | |
| | Oral | Non-applicable | Sediment (Marine water) | 26670 mg/kg | |
| 2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9 | STP | 100 mg/L | Fresh water | 0,635 mg/L | |
| | Soil | 0,29 mg/kg | Marine water | 0,064 mg/L | |
| | Intermittent | 6,35 mg/L | Sediment (Fresh water) | 3,29 mg/kg | |
| | Oral | Non-applicable | Sediment (Marine water) | 0,329 mg/kg | |
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | STP | 9,6 mg/L | Fresh water | 0,1 mg/L | |
| | Soil | 2,68 mg/kg | Marine water | 0,01 mg/L | |
| | Intermittent | 0,1 mg/L | Sediment (Fresh water) | 13,7 mg/kg | |
| | Oral | 0,02 g/kg | Sediment (Marine water) | 1,37 mg/kg | |

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation

ORS128 UTWARDZACZ DO PODKŁADU WYSOKOWYPEŁNIAJĄCEGO

Printing: 20/10/2021

Date of compilation: 20/10/2021

Version: 1

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)



| Identification | | | | |
|---------------------------------------------------------------|--------------|----------------|-------------------------|----------------|
| Hexamethylene-di-isocyanate CAS: 822-06-0 EC: 212-485-8 | STP | 8,42 mg/L | Fresh water | Non-applicable |
| | Soil | Non-applicable | Marine water | Non-applicable |
| | Intermittent | Non-applicable | Sediment (Fresh water) | Non-applicable |
| | Oral | Non-applicable | Sediment (Marine water) | Non-applicable |

8.2 Exposure controls:



A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection



| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|-----------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------|-----------------------------------------------------------------------------------|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  Mandatory respiratory tract protection | Filter mask for gases and vapours (Filter type: A) |  | EN 405:2002+A1:2010 | Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. |

C.- Specific protection for the hands





| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  Mandatory hand protection | NON-disposable chemical protective gloves (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.4 mm) |  | EN ISO 374-1:2016+A1:2018 EN 16523-1:2015+A1:2018 EN 420:2004+A1:2010 | The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin. |

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.



D.- Ocular and facial protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------|---------------------------------------------------------------------------------------------------------------------------|
|  Mandatory face protection | Panoramic glasses against splash/projections. |  | EN 166:2002 EN ISO 4007:2018 | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. |

E.- Body protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|---------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|
|  Mandatory complete body protection | Disposable clothing for protection against chemical risks, with antistatic and fireproof properties |  | EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994 | For professional use only. Clean periodically according to the manufacturer's instructions. |
|  Mandatory foot protection | Safety footwear for protection against chemical risk, with antistatic and heat resistant properties |  | EN ISO 13287:2013 EN ISO 20345:2011 EN 13832-1:2019 | Replace boots at any sign of deterioration. |

F.- Additional emergency measures

| Emergency measure | Standards | Emergency measure | Standards |
|---------------------------------------------------------------------------------------------------------|-------------------------------------------------|----------------------------------------------------------------------------------------------------------|------------------------------------------------|
|  Emergency shower | ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011 |  Eyewash stations | DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011 |

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation

ORS128 UTWARDZACZ DO PODKŁADU WYSOKOWYPEŁNIAJĄCEGO

Printing: 20/10/2021

Date of compilation: 20/10/2021

Version: 1

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

| | |
|---------------------------|---------------------------------------|
| V.O.C. (Supply): | 64,28 % weight |
| V.O.C. density at 20 °C: | 615,73 kg/m ³ (615,73 g/L) |
| Average carbon number: | 7,64 |
| Average molecular weight: | 114,61 g/mol |

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

| | |
|--------------------------|------------------|
| Physical state at 20 °C: | Liquid |
| Appearance: | Viscous |
| Colour: | Colourless |
| Odour: | Not available |
| Odour threshold: | Non-applicable * |

Volatility:

| | |
|----------------------------------------|-----------------------|
| Boiling point at atmospheric pressure: | 143 °C |
| Vapour pressure at 20 °C: | 603 Pa |
| Vapour pressure at 50 °C: | 3392,36 Pa (3,39 kPa) |
| Evaporation rate at 20 °C: | Non-applicable * |

Product description:

| | |
|----------------------------------------------|---------------------------------|
| Density at 20 °C: | 936,9 - 978,9 kg/m ³ |
| Relative density at 20 °C: | Non-applicable * |
| Dynamic viscosity at 20 °C: | 3000 cP |
| Kinematic viscosity at 20 °C: | 3111,28 mm ² /s |
| Kinematic viscosity at 40 °C: | >20,5 mm ² /s |
| Concentration: | Non-applicable * |
| pH: | Non-applicable * |
| Vapour density at 20 °C: | Non-applicable * |
| Partition coefficient n-octanol/water 20 °C: | Non-applicable * |
| Solubility in water at 20 °C: | Non-applicable * |
| Solubility properties: | Non-applicable * |
| Decomposition temperature: | Non-applicable * |
| Melting point/freezing point: | Non-applicable * |

Flammability:

| | |
|----------------------------|------------------|
| Flash Point: | 31 °C |
| Flammability (solid, gas): | Non-applicable * |
| Autoignition temperature: | 315 °C |
| Lower flammability limit: | Not available |
| Upper flammability limit: | Not available |

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation

ORS128 UTWARDZACZ DO PODKŁADU WYSOKOWYPEŁNIAJĄCEGO

Printing: 20/10/2021

Date of compilation: 20/10/2021

Version: 1

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Particle characteristics:

Median equivalent diameter: Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties: Non-applicable *

Oxidising properties: Non-applicable *

Corrosive to metals: Non-applicable *

Heat of combustion: Non-applicable *

Aerosols-total percentage (by mass) of flammable components: Non-applicable *

Other safety characteristics:

Surface tension at 20 °C: Non-applicable *

Refraction index: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

| Shock and friction | Contact with air | Increase in temperature | Sunlight | Humidity |
|--------------------|------------------|-------------------------|---------------------|----------------|
| Not applicable | Not applicable | Risk of combustion | Avoid direct impact | Not applicable |

10.5 Incompatible materials:

| Acids | Water | Oxidising materials | Combustible materials | Others |
|--------------------|----------------|---------------------|-----------------------|-------------------------------|
| Avoid strong acids | Not applicable | Avoid direct impact | Not applicable | Avoid alkalis or strong bases |

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation

ORS128 UTWARDZACZ DO PODKŁADU WYSOKOWYPEŁNIAJĄCEGO

Printing: 20/10/2021

Date of compilation: 20/10/2021

Version: 1

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Acute toxicity : Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
IARC: Xylene (3); Ethylbenzene (2B); Hydrocarbons, C9, aromatics (3)
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
 - Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) - single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.
- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
 - Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

| Identification | Acute toxicity | | Genus |
|---------------------------------------------------------------------------|-----------------|----------------------|--------|
| Hexamethylene diisocyanate, oligomers CAS: 28182-81-2 EC: 931-274-8 | LD50 oral | 5100 mg/kg | Rat |
| | LD50 dermal | >2000 mg/kg | |
| | LC50 inhalation | 11 mg/L (4 h) (ATEi) | |
| 2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9 | LD50 oral | 8532 mg/kg | Rat |
| | LD50 dermal | 5100 mg/kg | Rat |
| | LC50 inhalation | 30 mg/L (4 h) | Rat |
| Xylene CAS: 1330-20-7 EC: 215-535-7 | LD50 oral | 2100 mg/kg | Rat |
| | LD50 dermal | 1100 mg/kg | Rat |
| | LC50 inhalation | 11 mg/L (4 h) (ATEi) | |
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | LD50 oral | 3500 mg/kg | Rat |
| | LD50 dermal | 15354 mg/kg | Rabbit |
| | LC50 inhalation | 17,2 mg/L (4 h) | Rat |
| Hydrocarbons, C9, aromatics CAS: 64742-95-6 EC: 918-668-5 | LD50 oral | >2000 mg/kg | |
| | LD50 dermal | >2000 mg/kg | |
| | LC50 inhalation | >20 mg/L (4 h) | |
| Hexamethylene-di-isocyanate CAS: 822-06-0 EC: 212-485-8 | LD50 oral | >2000 mg/kg | |
| | LD50 dermal | >2000 mg/kg | |
| | LC50 inhalation | 3 mg/L (4 h) (ATEi) | Rat |

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation

ORS128 UTWARDZACZ DO PODKŁADU WYSOKOWYPEŁNIAJĄCEGO

Printing: 20/10/2021

Date of compilation: 20/10/2021

Version: 1

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

| Identification | Concentration | | Species | Genus |
|---------------------------------------------------------------------------|---------------|------------------|-------------------------|------------|
| Xylene CAS: 1330-20-7 EC: 215-535-7 | LC50 | >10 - 100 (96 h) | | Fish |
| | EC50 | >10 - 100 (48 h) | | Crustacean |
| | EC50 | >10 - 100 (72 h) | | Algae |
| Hexamethylene diisocyanate, oligomers CAS: 28182-81-2 EC: 931-274-8 | LC50 | Non-applicable | | |
| | EC50 | Non-applicable | | |
| | EC50 | 1000 mg/L (72 h) | Scenedesmus subspicatus | Algae |
| 2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9 | LC50 | 161 mg/L (96 h) | Pimephales promelas | Fish |
| | EC50 | 481 mg/L (48 h) | Daphnia sp. | Crustacean |
| | EC50 | Non-applicable | | |
| Hydrocarbons, C9, aromatics CAS: 64742-95-6 EC: 918-668-5 | LC50 | >1 - 10 (96 h) | | Fish |
| | EC50 | >1 - 10 (48 h) | | Crustacean |
| | EC50 | >1 - 10 (72 h) | | Algae |
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | LC50 | 42.3 mg/L (96 h) | Pimephales promelas | Fish |
| | EC50 | 75 mg/L (48 h) | Daphnia magna | Crustacean |
| | EC50 | 63 mg/L (3 h) | Chlorella vulgaris | Algae |

Chronic toxicity:

| Identification | Concentration | | Species | Genus |
|----------------------------------------------------------------|---------------|----------------|---------------------|------------|
| Xylene CAS: 1330-20-7 EC: 215-535-7 | NOEC | 1.3 mg/L | Oncorhynchus mykiss | Fish |
| | NOEC | 1.17 mg/L | Ceriodaphnia dubia | Crustacean |
| 2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9 | NOEC | 47.5 mg/L | Oryzias latipes | Fish |
| | NOEC | 100 mg/L | Daphnia magna | Crustacean |
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | NOEC | Non-applicable | | |
| | NOEC | 0.96 mg/L | Ceriodaphnia dubia | Crustacean |

12.2 Persistence and degradability:

| Identification | Degradability | | Biodegradability | |
|-------------------------------------------------------------------|---------------|----------------|------------------|----------------|
| | | | | |
| Xylene CAS: 1330-20-7 EC: 215-535-7 | BOD5 | Non-applicable | Concentration | Non-applicable |
| | COD | Non-applicable | Period | 28 days |
| | BOD5/COD | Non-applicable | % Biodegradable | 88 % |
| 2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9 | BOD5 | Non-applicable | Concentration | 785 mg/L |
| | COD | Non-applicable | Period | 8 days |
| | BOD5/COD | Non-applicable | % Biodegradable | 100 % |

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation

ORS128 UTWARDZACZ DO PODKŁADU WYSOKOWYPEŁNIAJĄCEGO

Printing: 20/10/2021

Date of compilation: 20/10/2021

Version: 1

SECTION 12: ECOLOGICAL INFORMATION (continued)

| Identification | Degradability | | Biodegradability | |
|---------------------------------------------------------------|---------------|----------------|------------------|----------|
| | Parameter | Value | Parameter | Value |
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | BOD5 | Non-applicable | Concentration | 100 mg/L |
| | COD | Non-applicable | Period | 14 days |
| | BOD5/COD | Non-applicable | % Biodegradable | 90 % |
| Hexamethylene-di-isocyanate CAS: 822-06-0 EC: 212-485-8 | BOD5 | Non-applicable | Concentration | 100 mg/L |
| | COD | Non-applicable | Period | 28 days |
| | BOD5/COD | Non-applicable | % Biodegradable | 28 % |

12.3 Bioaccumulative potential:

| Identification | Bioaccumulation potential | |
|-------------------------------------------------------------------|---------------------------|-------|
| | Parameter | Value |
| Xylene CAS: 1330-20-7 EC: 215-535-7 | BCF | 9 |
| | Pow Log | 2.77 |
| | Potential | Low |
| 2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9 | BCF | 1 |
| | Pow Log | 0.43 |
| | Potential | Low |
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | BCF | 1 |
| | Pow Log | 3.15 |
| | Potential | Low |

12.4 Mobility in soil:

| Identification | Absorption/desorption | | Volatility | |
|------------------------------------------------|-----------------------|----------------------|------------|-------------------------------|
| | Parameter | Value | Parameter | Value |
| Xylene CAS: 1330-20-7 EC: 215-535-7 | Koc | 202 | Henry | 524,86 Pa·m ³ /mol |
| | Conclusion | Moderate | Dry soil | Yes |
| | Surface tension | Non-applicable | Moist soil | Yes |
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | Koc | 520 | Henry | 798,44 Pa·m ³ /mol |
| | Conclusion | Moderate | Dry soil | Yes |
| | Surface tension | 2,859E-2 N/m (25 °C) | Moist soil | Yes |

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

| Code | Description | Waste class (Regulation (EU) No 1357/2014) |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------|
| 08 01 11* 15 01 10* | waste paint and varnish containing organic solvents or other hazardous substances packaging containing residues of or contaminated by hazardous substances | Dangerous |

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP13 Sensitising, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation

ORS128 UTWARDZACZ DO PODKŁADU WYSOKOWYPEŁNIAJĄCEGO

Printing: 20/10/2021

Date of compilation: 20/10/2021

Version: 1

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:



- 14.1 UN number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
Special regulations: 163, 367, 650
Tunnel restriction code: D/E
Physico-Chemical properties: see section 9
Limited quantities: 5 L
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 39-18:



- 14.1 UN number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Marine pollutant:** No
- 14.6 Special precautions for user**
Special regulations: 223, 955, 163, 367
EmS Codes: F-E, S-E
Physico-Chemical properties: see section 9
Limited quantities: 5 L
Segregation group: Non-applicable
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2021:



- 14.1 UN number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
Physico-Chemical properties: see section 9
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable
 Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable
 Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation

ORS128 UTWARDZACZ DO PODKŁADU WYSOKOWYPEŁNIAJĄCEGO

Printing: 20/10/2021

Date of compilation: 20/10/2021

Version: 1

SECTION 15: REGULATORY INFORMATION (continued)

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

| Section | Description | Lower-tier requirements | Upper-tier requirements |
|---------|-------------------|-------------------------|-------------------------|
| P5c | FLAMMABLE LIQUIDS | 5000 | 50000 |

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation

ORS128 UTWARDZACZ DO PODKŁADU WYSOKOWYPEŁNIAJĄCEGO

Printing: 20/10/2021

Date of compilation: 20/10/2021

Version: 1

SECTION 15: REGULATORY INFORMATION (continued)

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Contains more than 0.1 % of Hexamethylene-di-isocyanate, Hexamethylene diisocyanate, oligomers by weight. 1. Shall not be used as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 August 2023, unless:

(a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or (b) the employer or self-employed ensures that industrial or professional user(s) have successfully completed training on the safe use of diisocyanates prior to the use of the substance(s) or mixture(s).

2. Shall not be placed on the market as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 February 2022, unless:

(a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or (b) the supplier ensures that the recipient of the substance(s) or mixture(s) is provided with information on the requirements referred to in point (b) of paragraph 1 and the following statement is placed on the packaging, in a manner that is visibly distinct from the rest of the label information: "As from 24 August 2023 adequate training is required before industrial or professional use".

3. For the purpose of this entry "industrial and professional user(s)" means any worker or self-employed worker handling diisocyanates on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) or supervising these tasks.

4. The training referred to in point (b) of paragraph 1 shall include the instructions for the control of dermal and inhalation exposure to diisocyanates at the workplace without prejudice to any national occupational exposure limit value or other appropriate risk management measures at national level. Such training shall be conducted by an expert on occupational safety and health with competence acquired by relevant vocational training. That training shall cover as a minimum:

(a) the training elements in point (a) of paragraph 5 for all industrial and professional use(s).

(b) the training elements in points (a) and (b) of paragraph 5 for the following uses:

- handling open mixtures at ambient temperature (including foam tunnels)
- spraying in a ventilated booth
- application by roller
- application by brush
- application by dipping and pouring
- mechanical post treatment (e.g. cutting) of not fully cured articles which are not warm anymore
- cleaning and waste
- any other uses with similar exposure through the dermal and/or inhalation route

(c) the training elements in points (a), (b) and (c) of paragraph 5 for the following uses:

- handling incompletely cured articles (e.g. freshly cured, still warm)
- foundry applications
- maintenance and repair that needs access to equipment
- open handling of warm or hot formulations (> 45 °C)
- spraying in open air, with limited or only natural ventilation (includes large industry working halls) and spraying with high energy (e.g. foams, elastomers)
- and any other uses with similar exposure through the dermal and/or inhalation route.

5. Training elements:

(a) general training, including on-line training, on:

- chemistry of diisocyanates
- toxicity hazards (including acute toxicity)
- exposure to diisocyanates
- occupational exposure limit values
- how sensitisation can develop
- odour as indication of hazard
- importance of volatility for risk
- viscosity, temperature, and molecular weight of diisocyanates
- personal hygiene
- personal protective equipment needed, including practical instructions for its correct use and its limitations
- risk of dermal contact and inhalation exposure
- risk in relation to application process used
- skin and inhalation protection scheme
- ventilation
- cleaning, leakages, maintenance
- discarding empty packaging
- protection of bystanders
- identification of critical handling stages
- specific national code systems (if applicable)

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation

ORS128 UTWARDZACZ DO PODKŁADU WYSOKOWYPEŁNIAJĄCEGO

Printing: 20/10/2021

Date of compilation: 20/10/2021

Version: 1

SECTION 15: REGULATORY INFORMATION (continued)

- behaviour-based safety
- certification or documented proof that training has been successfully completed
- (b) intermediate level training, including on-line training, on:
 - additional behaviour-based aspects
 - maintenance
 - management of change
 - evaluation of existing safety instructions
 - risk in relation to application process used
- certification or documented proof that training has been successfully completed

(c) advanced training, including on-line training, on:

- any additional certification needed for the specific uses covered
- spraying outside a spraying booth
- open handling of hot or warm formulations (> 45 °C)
- certification or documented proof that training has been successfully completed

6. The training shall comply with the provisions set by the Member State in which the industrial or professional user(s) operate. Member States may implement or continue to apply their own national requirements for the use of the substance(s) or mixture(s), as long as the minimum requirements set out in paragraphs 4 and 5 are met.

7. The supplier referred to in point (b) of paragraph 2 shall ensure that the recipient is provided with training material and courses pursuant to paragraphs 4 and 5 in the official language(s) of the Member State(s) where the substance(s) or mixture(s) are supplied. The training shall take into consideration the specificity of the products supplied, including composition, packaging, and design.

8. The employer or self-employed shall document the successful completion of the training referred to in paragraphs 4 and 5. The training shall be renewed at least every five years.

9. Member States shall include in their reports pursuant to Article 117(1) the following information:

- (a) any established training requirements and other risk management measures related to the industrial and professional uses of diisocyanates foreseen in national law
- (b) the number of cases of reported and recognised occupational asthma and occupational respiratory and dermal diseases in relation to diisocyanates
- (c) national exposure limits for diisocyanates, if there are any
- (d) information about enforcement activities related to this restriction.

10. This restriction shall apply without prejudice to other Union legislation on the protection of safety and health of workers at the workplace.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

Texts of the legislative phrases mentioned in section 2:

H317: May cause an allergic skin reaction.

H335: May cause respiratory irritation.

H315: Causes skin irritation.

H412: Harmful to aquatic life with long lasting effects.

H373: May cause damage to organs through prolonged or repeated exposure (Oral).

H332: Harmful if inhaled.

H226: Flammable liquid and vapour.

H319: Causes serious eye irritation.

Texts of the legislative phrases mentioned in section 3:

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation

ORS128 UTWARDZACZ DO PODKŁADU WYSOKOWYPEŁNIAJĄCEGO

Printing: 20/10/2021

Date of compilation: 20/10/2021

Version: 1

SECTION 16: OTHER INFORMATION (continued)

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 3: H331 - Toxic if inhaled.

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.

Acute Tox. 4: H332 - Harmful if inhaled.

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

STOT SE 3: H335 - May cause respiratory irritation.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

Skin Sens. 1: Calculation method

STOT SE 3: Calculation method

Skin Irrit. 2: Calculation method

Aquatic Chronic 3: Calculation method

STOT RE 2: Calculation method

Acute Tox. 4: Calculation method

Flam. Liq. 3: Calculation method (2.6.4.3)

Eye Irrit. 2: Calculation method

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -