

Barracuda 115NI/min

ϕ [mm]	1 [bar]	1,2 [bar]	1,5 [bar]
1,5	10÷20 HP	10÷20 HP	10÷20 HP
1,6			
1,7			
1,8			
1,9	20÷30 HP	20÷30 HP	20÷30 HP
2,0			
2,1			
2,2			
2,3	30÷40 HP	30÷40 HP	30÷40 HP
2,4			
2,5			
2,6			
2,7	30÷40 HP	40÷45 HP	40÷45 HP
2,8			
2,9			
b.d.			

Barracuda 130NI/min

ϕ [mm]	1 [bar]	1,2 [bar]	1,5 [bar]
1,5	10÷20 HP	10÷20 HP	10÷20 HP
1,6			
1,7			
1,8			
1,9	20÷30 HP	20÷30 HP	20÷30 HP
2,0			
2,1			
2,2			
2,3	30÷40 HP	30÷40 HP	30÷40 HP
2,4			
2,5			
2,6			
2,7	30÷40 HP	40÷45 HP	40÷45 HP
2,8			
2,9			
3,0			
3,1	40÷45 HP	45÷50 HP	45÷50 HP
3,2			
3,3			
b.d.			



TABELE DOBORU DYSZ WTRYSKIWACZY