

LITEN EPX 00

GENERAL FEATURES:

LITEN® EPX semi-liquid gear lithium greases are based on mineral oil with the kinematic viscosity of ca. 150 mm²/s at 40°C.

Due to required better lubricating properties they are enriched with EP additives as well as additives increasing adherence, antioxidative and anticorrosive properties.

APPLICATION:

Liten® EPX greases are intended to lubricate closed toothed cylindrical and bevel gears working in the temperature range between -20°C and +100°C.

The selection of Liten® EPX grease depends on the design and sealing degree of the gear and working temperature.

- Liten® EPX 00 – is used in lower temperatures than given above and at good sealing of the gear,
- Liten® EPX 0 – is used in intermediate conditions,
- Liten® EPX 1- is used in higher temperatures than given above and at weak sealing of the gear.

STANDARDS, APPROVALS. SPECIFICATION:

DIN 51 502: GP00G-20 ISO 6743-9: BBEB-00

PARAMETERS	UNIT	TYPICAL VALUES
NLGI class		00
Worked penetration at 25°C	mm/10	420
Penetration at - 20°C	mm/10	210
Dropping point	°C	173
Ability to transfer loads at the FZG	Breaking load	11

NOTE:

Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each product lot.

