



## PLATINUM GEAR SV 75W-80

Quality class: API: GL-4  
Viscosity grad: SAE: 75W-80

### GENERAL FEATURES:

Platinum Gear SV 75W-80 is a high quality synthetic gear oil. Application of the most modern Extreme Pressure additives provides the ability to carry heavy loads. Highest quality synthetic base oil guarantees excellent lubricating properties during the entire operation.

#### Guarantees:

- stability of the lubricating properties during operation,
- Excellent lubricating and anti-wear properties,
- The ability to carry heavy loads.

### APPLICATION:

Platinum SV Gear 75W-80 is dedicated for use gearboxes, transmissions and axles, in cars, trucks and heavy construction machinery.

### STANDARDS, APPROVALS. SPECIFICATION:

Meet requirements:  
Mercedes-Benz 235.5  
ZF TE-ML 01, 02, 08  
MAN 341 Z2  
DAF  
Iveco  
Eaton

PARAMETERS	UNIT	TYPICAL VALUES
SAE Viscosity Grade	-	75W-80
Kinematic viscosity at temperature 100°C	mm <sup>2</sup> /s	9,087
Viscosity index	-	154
Soldification point	°C	-41

#### NOTE:

Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each product lot.

