

PLATINUM GEAR SX 75W-90

Quality class: API: GL-5
Viscosity grad: SAE: 75W-90

GENERAL FEATURES:

Platinum Gear SX 75W-90 is a high-quality synthetic gear oil for lorries as well as for construction and farming machinery. Owing to its synthetic base oils, it provides consistent performance and protection for power trains throughout their entire lifetime. It guarantees:

- consistent lubrication properties during use
- good load bearing capacity
- excellent lubrication and anti-wear properties

APPLICATION:

Platinum Gear SX 75W-90 oil is intended for use mainly in final gears and rear drive axles.

STANDARDS, APPROVALS. SPECIFICATION:

Conforms to:
ZF TE-ML 05A
ZF TE-ML 7A
ZF TE-ML 12E
ZF TE-ML 16, B, C, D
ZF TE-ML 17B
ZF TE-ML 19B
ZF TE-ML 21A
NATO O-226

PARAMETERS	UNIT	TYPICAL VALUES
SAE viscosity class	-	75W-90
Kinematic viscosity at 100°C	mm ² /s	15,6
Viscosity index	-	153
Freezing point	°C	-40

NOTE:
Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each product lot.

